

Temporal Coherence Methods in Real-Time Rendering

Daniel Scherzer¹, Lei Yang², Oliver Mattausch^{3,4}, Diego Nehab⁵, Pedro V. Sander², Michael Wimmer³ and Elmar Eisemann⁶

¹MPI Informatik, ²Hong Kong UST, ³TU Vienna, ⁴U Zurich, ⁵IMPA, and ⁶Delft University of Technology/Telecom ParisTech scherzer@mpi-inf.mpg.de, yanglei@alumni.ust.hk, psander@cse.ust.hk, {matt, wimmer}@cg.tuwien.ac.at, diego@impa.br, elmar.eisemann@telecom-paristech.fr

Abstract

Nowadays, there is a strong trend towards rendering to higher-resolution displays and at high frame rates. This development aims at delivering more detail and better accuracy, but it also comes at a significant cost. Although graphics cards continue to evolve with an ever-increasing amount of computational power, the speed gain is easily counteracted by increasingly complex and sophisticated shading computations. For real-time applications, the direct consequence is that image resolution and temporal resolution are often the first candidates to bow to the performance constraints (e.g. although full HD is possible, PS3 and XBox often render at lower resolutions).

In order to achieve high-quality rendering at a lower cost, one can exploit temporal coherence (TC). The underlying observation is that a higher resolution and frame rate do not necessarily imply a much higher workload, but a larger amount of redundancy and a higher potential for amortizing rendering over several frames. In this survey, we investigate methods that make use of this principle and provide practical and theoretical advice on how to exploit TC for performance optimization. These methods not only allow incorporating more computationally intensive shading effects into many existing applications, but also offer exciting opportunities for extending high-end graphics applications to lower-spec consumer-level hardware. To this end, we first introduce the notion and main concepts of TC, including an overview of historical methods. We then describe a general approach, image-space reprojection, with several implementation algorithms that facilitate reusing shading information across adjacent frames. We also discuss data-reuse quality and performance related to reprojection techniques. Finally, in the second half of this survey, we demonstrate various applications that exploit TC in real-time rendering.

Keywords: anti-aliasing, frame interpolation, global illumination, image-based rendering, large data visualization, level-of-detail, non-photo-realistic rendering, occlusion culling, perception-based rendering, remote rendering, sampling, shadows, streaming, temporal coherence, upsampling

ACM CCS: I.3.3 [Computer Graphics]: Picture/Image Generation—Display Algorithms; Viewing Algorithms; I.3.7 [Computer Graphics]: Three-Dimensional Graphics and Realism—Color, shading, shadowing and texture

1. Introduction

In order to satisfy the ever-increasing market demand for richer gaming experiences, developers of real-time rendering applications are constantly looking for creative ways to fit increased photo-realism, frame rates and resolution within the computational budget offered by each new graphics hardware generation. Although graphics hardware evolved remarkably in the past decade, the general sense is that at least in the foreseeable future, any hardware improvement will be readily put to use towards one of these goals.

The immense computational power required to render a single frame with desirable effects such as physically correct shadows, depth-of-field, motion-blur and global illumination (or even an effective ambient-occlusion approximation) is

Computer Graphics Forum © 2012 The Eurographics Association and Blackwell Publishing Ltd. Published by Blackwell Publishing, 9600 Garsington Road, Oxford OX4 2DQ, UK and 350 Main Street, Malden, MA 02148, USA.

Figure 1: Real-time rendering applications exhibit a considerable amount of spatio-temporal coherence. This is true for camera motion, as in the Parthenon sequence (left), as well as animated scenes such as the Heroine (middle) and Ninja (right) sequences. Diagrams to the right of each rendering show disoccluded points in red, in contrast to points that were visible in the previous frame, which are shown in green (i.e. green points are available for reuse). [Images courtesy of Advanced Micro Devices, Inc., Sunnyvale, California, USA]

multiplied by the demands of high-resolution displays, which require large scene descriptions to be manipulated (geometry and textures). The difficulty is compounded further by the need to generate such frames continuously, as part of realtime animation.

Although rendering at 30 Hz (NTSC) is already considered real-time, most modern liquid crystal display (LCD) monitors and TVs can refresh at least at 60 Hz. Naturally, developers strive to meet this standard. Given that there is still a measurable task-performance improvement in interactive applications as frame rates increase up to 120 Hz [DER*10b], there is justification to target such high frame rates. In this case, as little as 8 ms are available to produce each complete photo-realistic image, and all involved calculations (including physical simulations and other tasks unrelated to rendering itself) have to fit within this time budget. Needless to say, this poses a difficult task.

The traditional approach to optimization in the context of real-time rendering is to focus on improving the performance of individual rendering tasks, one at a time. In this survey, we present results that are connected by a more general approach to optimization: exploiting temporal coherence (TC).

Consider the examples shown in Figure 1. When frame rates are high, there are only very small changes from one frame to the next. Each visible surface point tends to remain visible across the interval of several frames. Furthermore, point attributes (including colour) tend to maintain their values almost unchanged throughout. To measure the amount of TC in these animation sequences, Figure 2 plots the fraction of points that remain visible from one frame to the next. We can see that fractions of 90% and higher are typical.

Since an ever-increasing slice of the rendering budget is dedicated to shading surface points, such a high level of TC presents a great opportunity for optimization. Rather than wastefully recomputing every frame in its entirety from scratch, we can reuse information computed during the course of one frame (intermediate results, or even final colours) to help render the following frames. The resulting



Figure 2: Plot shows the percentage of surface points that remain visible from one frame to the next for the animations of Figure 1 Coherence in excess of 90% is typical of many game-like scenes.

reduction in the average cost of rendering a frame can be used in a variety of ways: from simply increasing the frame rate to improving the quality of each rendered frame.

Naturally, TC has been exploited since the early days of computer graphics. We describe a variety of early applications in Section 2. In Section 3, we move to methods that can be used to take advantage of TC in real-time rendering scenarios. Special attention is given to techniques based on reprojection. Reprojection allows us to map a surface point in one frame to the same surface point in a previously rendered frame. This mapping plays a key role in the reuse of information across frames. Reusing information involves certain quality/performance trade-offs that are analyzed in Section 4. Since the selection of a proper target for reuse can modulate this trade-off, the same section discusses the most important factors influencing this choice. In Section 5, we then categorize and discuss a number of applications that take advantage of TC in real-time rendering, including both the ones that use reprojection, and the ones that exploit TC in other spaces. Finally, in Section 6, we provide a summary of the presentation.

2. Early Approaches

TC has been around for almost as long as computer graphics itself. For example, the term *frame-to-frame coherence* was first introduced by Sutherland *et al.* [SSS74] in his seminal paper 'Characterization of Ten Hidden-Surface Algorithms'. Therefore, we will summarize early developments in which TC was already used in similar ways.

In particular, we will cover the use of TC in *ray-tracing*, *image-based rendering*, and *image and render caches*.

2.1. Ray-tracing

TC was already used for the classical ray-tracing algorithm in order to speed up the calculation of animation sequences. While these techniques are for offline rendering, most of them already make use of forward reprojection (Section 3.2) for reusing information.

Badt [BJ88] developed a forward reprojection algorithm that uses object space information stored from the previous frame. This allows approximating ray-traced animation frames of diffuse polygons. Adelson and Hodges [AH95] later extended the approach to ray-tracing of arbitrary scenes. Havran *et al.* [HBS03] reused ray/object intersections in raycasted walkthroughs. They do this by reprojecting and splatting visible point samples from the last frame into the current, thereby avoiding the costly ray traversal for more than 78% of the pixels in their test scenes.

Leaving the concept of frame-based rendering behind, Bishop *et al.* [BFMZ94] introduced frameless rendering, which heavily relies upon TC for sensible output. Here, each pixel is rendered independently based on the most recent input, thereby minimizing lag. There is no wait period until all pixels of a frame are drawn, but individual pixels stay visible for a random time span, until they are replaced with an updated pixel. Note that this approach does not use the object coherence that is an integral part of many polygon renderers. To avoid image tearing, pixels are rendered in a random order. Dayal *et al.* [DWWL05] combined this with temporal reprojection and adaptive reconstruction, focusing on edges and dynamic parts of the scene.

2.2. Image-based rendering

In a general sense, TC is also related to methods that replace parts of a scene with image-based proxy representations. This can be interpreted as a form of reverse reprojection (Section 3.1) applied to individual parts of a scene. This idea was used most prominently in the so-called hierarchical image cache and its variations [Sch96, SLS*96], where images (called impostors) of complex distant geometry are generated on the fly and reused in subsequent frames, thus reducing rendering times. The geometric error for such systems has also been formally analyzed [ED07a]. Frame-to-frame coherence is further exploited in various systems that partition the scene into different layers [RP94, LS97], while others augment the image-based representation with depth information [SGHS98]. In this report, however, we will focus on methods that do not use proxy geometry to cache information, but directly reuse rendered information from the previous frame buffers.

2.3. Image and render caches

Image and render caches store the information generated in previous frames in a data structure, and reuse this information for the generation of the current frame, using different reconstruction and mostly forward reprojection techniques (Section 3.2).

Wimmer *et al.* [WGS99] proposed a technique that accelerates the rendering of complex environments by splitting the scene into a near field and a far field: The near field is rendered using the traditional rendering pipeline, while ray casting is used for the far field. To minimize the number of rays cast, they use a *panoramic image cache* and only recompute rays if a cache entry is not valid anymore, where validity is based on the distance to the original observer position where the pixel was generated. The panoramic image cache avoids reprojection altogether, but quickly becomes inaccurate for translational motion.

Qu *et al.* [QWQK00] proposed using image warping to accelerate ray-casting. The idea is to warp the output image of the previous frame into the current frame using forward projection. Due to the warping, pixels may fall between the grid positions of the pixels of the current frame; therefore, an offset buffer is used to store the exact positions. Due to disocclusions, holes can occur at some pixels. Here, ray-casting is used to generate these missing pixels. The authors proposed to use an age stored with each pixel, which is increased with each warping step to account for the lower quality of pixels that have been warped (repeatedly). Upon rendering a new output frame, this age can be used to decide if a pixel should be re-rendered or reused.

Walter *et al.* [WDP99] introduced the *render cache*. It is intended as an acceleration data structure for renderers that are too slow for interactive use. In contrast to the previously mentioned approaches, which store pixel colours, the render cache is a point-based structure, which stores the complete 3D coordinates of rendered points and shading information. By using reverse reprojection, these results can be reused in the current frame. Progressive refinement allows decoupling the rendering and display frame rates, enabling high interactivity. Walter *et al.* [WDG02] extended this approach with predictive sampling and interpolation filters, while later work accelerated the render cache on the GPU [VALBW06, ZWL05].

Ward and Simmons [WS99] described the *Holodeck ray* cache, which converts rendered samples into a spherical 4D

mesh centred at the viewpoint. The mesh can then be displayed for different viewpoints. Based on this method, Simmons and Séquin [SS00] proposed the *Tapestry* representation by introducing incremental re-centring of the spherical mesh, as well as other enhancements such as prioritized sampling and automatic sample invalidation.

3. Reprojection and Data Reuse

An important decision when utilizing TC is how the previously computed data are stored, tracked, retrieved and reused. On modern graphics hardware, the most common way is to store the desired data at visible surface points in viewportsized off-screen buffers at each rendered frame, usually referred to as history buffer, payload buffer or cache. When generating the following frames, the data in the buffer are reprojected to their new locations based on scene motion. Even with hardware support, reprojection can still be a computationally challenging task. In this section, we first describe two reprojection strategies that are commonly used in numerous applications and can sometimes be interchanged to suit special needs. In disoccluded regions where the previous data are not available, we show how to fill in approximate results that are visually plausible. Finally, we describe amortized sampling, which is a basis used in various applications described in Section 5.

3.1. Reverse reprojection

A basic scenario of using TC is to generate a new frame using data from a previously shaded frame. For each pixel in the new frame, we can trace back to its position in the earlier cached frame to determine if it was previously visible. If available, this cached value can be reused in place of performing an expensive computation. Otherwise it must be recomputed from scratch. This technique is called the *Reverse Reprojection Cache* (RRC). It was proposed independently by Nehab *et al.* [NSL*07] and Scherzer *et al.* [SJW07], and serves as a framework for a number of applications described in Section 5.

Formally, let f_t denote the cache generated at time t, which is a framebuffer holding the pixel data visible at that frame. In addition to f_t , we keep an accompanying buffer d_t which holds the scene depth in screen space. Let $f_t(\mathbf{p})$ and $d_t(\mathbf{p})$ denote the buffer values at pixel $\mathbf{p} \in \mathbb{Z}^2$. For each pixel $\mathbf{p} = (x, y)$ at time t, we determine the 3D clip-space position of its generating scene point at frame t - 1, denoted by $(x', y', z') = \pi_{t-1}(\mathbf{p})$. Here, the reprojection operator $\pi_{t-1}(\mathbf{p})$ maps a point \mathbf{p} to its previous position at frame t - 1. Note that with this reprojection operation, we also obtain the depth of the generating scene point z' at frame t - 1. This depth is used to test whether the current point was visible in the previous frame. If the reprojected depth z' equals $d_{t-1}(x', y')$ (within a given tolerance), we conclude that the current pixel



Figure 3: The reverse reprojection operator. The shading result and pixel depths of time t - 1 are stored in screen-space framebuffers (left). For each pixel \mathbf{p} at time t (right), its reprojected position $\pi_{t-1}(\mathbf{p})$ is computed to locate the corresponding position at frame t - 1. The recomputed scene depth is compared to the stored pixel depth. A pair of matching depths indicate a cache hit (\mathbf{p}_2), whereas inconsistent depths indicate a cache miss (\mathbf{p}_1).

p and the reprojected pixel $f_{t-1}(x', y')$ are indeed generated by the same surface point. In this case, the previous value can be reused. Otherwise no correspondence exists and we denote this by $\pi_{t-1}(\mathbf{p}) = \emptyset$, which we refer to as a *cache miss*. Additional tests such as object-ID equality can also be employed to reinforce this cache miss decision. The reverse reprojection operation is illustrated in Figure 3.

3.1.1. Implementation

The RRC algorithm can be conveniently mapped to the modern programmable rendering pipeline. A major task of this is to compute the reprojection operator $\pi_{t-1}(\mathbf{p})$, which maps each pixel **p** to its corresponding clip-space position in the previous frame t - 1. At frame t, the homogeneous projection space coordinates $(x_t, y_t, z_t, w_t)_{vert}$ of each vertex v are calculated in the vertex shader, to which the application has provided the world, view and projection matrices and any animation parameters. To perform correct reprojection, the application also has to provide these matrices and animation parameters at t-1to the vertex shading stage. In addition to transforming the vertex at frame t, the vertex shader also transforms the vertex using the matrices and parameters from frame t-1, thereby computing the projection-space coordinates $(x_{t-1}, y_{t-1}, z_{t-1}, w_{t-1})_{vert}$ of the same vertex at frame t - 1. These coordinates are stored as vertex attributes and are automatically interpolated by the hardware before reaching the pixel stage. This gives each pixel **p** access to the previous projection-space coordinates $(x_{t-1}, y_{t-1}, z_{t-1}, w_{t-1})_{pix}$. The final cache coordinate $\pi_{t-1}(\mathbf{p})$ is obtained with a simple division by $(w_{t-1})_{pix}$ within the pixel shader. Note that the transformation need only be computed at the vertex level, thereby significantly reducing the computational overhead in most scenes.

Because of arbitrary scene motion and animation, the previous position $\pi_{t-1}(\mathbf{p})$ usually lies somewhere between the set of discrete samples in the cache f_{t-1} , and thus some form of resampling is required. Nehab *et al.* [NSL*07] suggested using hardware-assisted bilinear texture fetch for resampling. In most situations, this suffices for practical use. It is also used to reconstruct the previous depth value so that a more robust cache-miss detection can be achieved.

3.2. Forward reprojection

Alternatively, instead of starting from every pixel in the target frame, we can directly process the cache and map every pixel in the cache to its new position. This has the advantage that it does not require processing the scene geometry for the new frame, which is desirable in some applications. Still, it requires a forward motion vector (or disparity vector) generated for each pixel, which is equivalent to the inverse mapping of $\pi_{t-1}(\mathbf{p})$.

On the other hand, per-pixel forward projection can be difficult and costly to implement on conventional graphics hardware (prior to DirectX 11) because it involves a scattering operation, which does not map well to the traditional graphics pipeline. For example, splatting each pixel from the previous frame to its reprojected position in the current frame can be slow and leave holes. It may also require applying complex filtering strategies in order to obtain pixel-accurate results. A way around these problems was described by Didyk et al. [DER*10b]: they proposed an image-warping technique, which is efficient on conventional GPUs. The warping is achieved by approximating the motion vector field with a coarse grid representation, assuming that the vector field is piecewise linear. An initial uniform grid is snapped to large motion vector discontinuities in the previous frame. Then, the grid geometry is rendered to its new position dictated by the motion vector field so that its associated texture is automatically warped. Occlusion and disocclusion are naturally handled with grid folding and stretching. Note that depth testing must be enabled in order to correctly resolve occlusions and fold-overs.

A regular grid used by Didyk *et al.* [DER*10b] can have difficulties warping images with finely detailed geometry. They later proposed an improved algorithm using adaptive grids [DRE*10]. Their new approach starts with a regular grid (32×32) . Then a geometry shader traverses all the quads in the grid in parallel. Every quad that contains a discontinuity is further partitioned in four. This process is iterated until no quads need to be further partitioned. At that point, the grid geometry is rendered as in the regular grid case. Due to the adaptive grid, this new approach has better utilization of computational resources, thereby significantly improving the quality.

Yu *et al.* [YWY10] proposed a forward reprojection method that leverages the parallel data scattering function-

ality on the GPU (available through CUDA or DirectX 11 Compute Shader). For each pixel in the cache, they determine its new position in the target frame by offsetting its current position using the forward motion vector (disparity vector). Then, the depth of the current pixel is tested against the target pixel for resolving visibility. This operation is performed using the atomic min functionality to avoid parallel write conflicts. Note that since there is no one-to-one mapping between the source and the target pixels, holes can be present after reprojection. To resolve this, Yu *et al.* [YWY10] proposed to increase the support size of the reprojected pixel, i.e. to write to all four neighbours of each reprojected fractional position. This works with near-view warping for their application of light-field generation, but may be insufficient for other applications where non-uniform motion is involved.

Recently, Yang *et al.* [YTS*11] proposed an image-based approach for forward reprojection using conventional GPU pixel-shading functionality, i.e. pixel gathering as opposed to scattering. The essence of the approach is an iterative image-space search performed independently at each pixel in the target frame, in order to find the motion vector that leads to the corresponding pixels in the rendered frames. This approach effectively inverts the reprojection operator $\pi_{t-1}(\mathbf{p})$ based on the assumption that $\pi_{t-1}(\mathbf{p})$ is piecewise smooth over the image. Discontinuity is handled by several additional search initialization heuristics. The entire process fits in a pixel shader and produces convincing results within a small time budget.

3.3. Handling disocclusion

The process of reprojection is essentially a non-linear warping and may leave the newly disoccluded regions incorrectly shaded or blank. With reverse reprojection, we may have the option to reshade these regions whenever a cache miss occurs. However, this is not always desirable due to limited time budget or other constraints imposed by the application. With forward reprojection, there is usually no such option since the shading input may not be available. Therefore, some form of approximate hole filling needs to be performed in order to reduce visual artefacts.

Andreev [And10] suggested an inpainting strategy that duplicates and offsets neighbouring image patches into the hole area from the four sides. This is efficiently implemented in a pixel shader and can be performed iteratively until the hole is completely filled. For a more robust solution, one can consider using pull–push interpolation [MKC07]. The pull–push algorithm consists of a pull phase and a subsequent push phase. The pull phase iteratively computes coarser levels of the image containing holes, forming an image pyramid. Each pixel in a coarser level is the average of the valid pixels in the corresponding four pixels from the finer level. The push phase then operates in the inverse order and interpolates the hole pixels from the coarser levels. This works best for the



Figure 4: Schematic diagram of applying the RRC to avoid pixel shading whenever possible [NSL*07].

small holes caused by per-pixel forward reprojection. With larger holes, the interpolated pixels may appear blurred and can be a source of artefacts as well.

3.4. Cache refresh

A straightforward usage of data reprojection is to avoid shading pixels that are visible in the previous frame. This can apply to either part or the entire pixel shading computation. For example, if we use RRC, the original pixel shader can be modified to add a cache load and reuse branch, as shown in Figure 4. When each pixel **p** is generated, the reprojection shader fetches the value at $\pi_{t-1}(\mathbf{p})$ in the cache and tests if the result is valid (i.e. a cache hit). If so, the shader can reuse this value in the calculation of the final pixel colour. Otherwise, the shader executes the normal pixel shading. Whichever route the shader follows, it always stores the cacheable value for potential reuse during the following frame.

Although a cached value can be continuously reused throughout many frames, it may quickly become stale because of either shading changes or resampling error. Nehab *et al.* [NSL*07] proposed to refresh (i.e. recompute) the value periodically in order to counteract this effect. For a fixed refresh rate, the screen can be divided into Δn groups and updated in a round-robin fashion in each frame by testing the following condition for each pixel:

$$(t+i) \mod \Delta n = 0, \tag{1}$$

where i is the group ID of the pixel and t is a global clock. They suggest two simple ways of dividing the screen:

- The screen is partitioned into a grid of Δn nonoverlapping tiles, with pixels in a tile sharing the same ID.
- The screen pixels are equally partitioned into Δn groups with each pixel assigned a random group ID.
- The updated screen pixels are uniformly distributed on a regular grid. For a static scene and camera, interleaving *n* such images leads to an accurate high-resolution image of the scene.

With the tiled refresh strategy, pixels within a tile are refreshed at the same time. This leads to excellent refresh coher-



Figure 5: Three control flow strategies for accelerating pixel shading using the RRC.

ence, but may lead to visible discontinuity at tile boundaries. The randomly distributed refresh strategy updates pixels in a random pattern. It exchanges sharp discontinuities for high-frequency noise, which is usually less objectionable. Note that it is recommended to assign the same ID to each 2×2 or larger quad of pixels, because modern GPUs perform lock-step shading computation on such quads. The interleaved refresh regions are easy to achieve by rendering low-resolution frames and applying a distance-dependent offset on the geometry. For temporal integration, such schemes are interesting, as the combination of these samples leads to a high-resolution shot.

In addition, care must be taken in order to maximize the performance when implementing this scheme with RRC. The fact that there are two distinct paths in Figure 4, cache hit and cache miss, allows for several implementation alternatives. The most straightforward approach is to branch between the two paths (Figure 5a). This allows all the tasks to be performed in a single rendering pass, but may suffer from dynamic branching inefficiency particularly when the refreshed region is not coherent and the branches are unbalanced. To achieve better performance, Nehab et al. [NSL*07] defer the expensive recomputation and put it into a separate pass so that the branches are more balanced (Figure 5b). By relying on early-Z culling, the miss shader is only executed on the cache-miss pixels that are automatically grouped to avoid any performance penalty. If the hit shader (green block in Figure 5) is also non-trivial to compute, the branches in the first pass may still not be balanced. Sitthi-amorn *et al.* [SaLY*08a] proposed a method that further separates this part of the computation into a third pass (Figure 5c) in order to reduce dynamic branching cost. This three-pass implementation also has the advantage that it does not require multiple render-target support, but incurs more geometry processing cost. The choice of strategy therefore depends on the relative cost between vertex and pixel shading in the target scene. Sitthi-amorn *et al.* [SaLY*08a] presented some empirical performance analysis of these three implementations in practice.

3.5. Amortized sampling

Another common strategy of data reuse is to combine previous shading results with those from the current frame. Gradual phase-out can then be used to avoid explicitly refreshing pixels. This strategy is usually applied to amortize the expensive task of computing a Monte-Carlo integral, in which multiple spatial samples are combined for each pixel. With data from the past, each frame then only needs to compute a lot less samples (typically only one) for each pixel in order to achieve a similar image quality. This is beneficial for many high-quality rendering effects described later, such as spatial anti-aliasing, soft shadows and global illumination.

In order to efficiently reuse and combine previously computed samples of a signal without increasing storage overhead, Nehab *et al.* [NSL*07] and Scherzer *et al.* [SJW07] proposed to combine and store all previously computed samples associated with a surface point using a single running average. In each frame, only one sample $s_t(\mathbf{p})$ is computed for each pixel \mathbf{p} and is combined with this running average using a recursive exponential smoothing filter:

$$f_t(\mathbf{p}) \leftarrow (\alpha) s_t(\mathbf{p}) + (1-\alpha) f_{t-1}(\pi_{t-1}(\mathbf{p})).$$
 (2)

Here, the running estimate of frame *t* is represented by f_t and is stored in the RRC, and s_t denotes the shading contribution from the current frame. If we expand this recursive formulation, we can see that the running estimate is equivalent to the weighted sum of all the previous samples at the same surface point. The weight of a single sample decreases exponentially over time, and the smoothing factor α regulates the trade-off between the degree of variance reduction and responsiveness to changes in the sampled signal. For example, a small value of α leads to a relatively slow decrease of the sample weights, which effectively accumulates more samples in the past and therefore produces a smoother result at the expense of additional lag in the shaded signal.

The precise degree of variance reduction is given by

$$\lim_{t \to \infty} \frac{\operatorname{Var}\left(f_t(\mathbf{p})\right)}{\operatorname{Var}\left(s_t(\mathbf{p})\right)} = \frac{\alpha}{2 - \alpha}.$$
(3)

For example, choosing a value of $\alpha = 2/5$ reduces the variance to 1/4 the original. This is roughly equivalent to increas-



Figure 6: Trade-off between the amount of variance reduction (the variance ratio curve), and the maximum frames of lag that may exist in the current estimate (the total falloff curve) [NSL*07]. This trade-off is controlled by the parameter α .

ing the sampling rate by a factor of 4. On the other hand, the actual number of frames contributing to f_t with non-trivial weights (i.e. larger than 8-bit precision 1/256) is 10, which indicates that the contribution of any obsolete sample will be smoothed out after 10 frames. This trade-off between smoothness and lag is illustrated in Figure 6. In practice, α must be carefully set to obtain the best trade-off.

4. Data-Reuse Quality and Performance

The ideal scenario for taking advantage of coherence is when the value of interest obtained from a previous frame is exactly the same as the desired one. In reality, when considering a target for reuse, we often find that its value depends on inputs that are beyond our control. These may include changing viewing parameters, lighting conditions, time itself, and most importantly, user interactions. Good targets for reuse are those that change little under the range of expected input variation. Nevertheless, even slowly varying attributes must be eventually updated, and we must also identify appropriate refresh periods.

Another important consideration is the cost of recomputing each reused value. This is because the overhead associated with obtaining previously computed values is not negligible (see Section 3.1.1). If recomputing a value is cheap, reusing it may not bring any performance advantage.

In summary, developers must identify computationally expensive intermediate computations that vary little under the range of expected input changes, and determine the appropriate number of frames between updates. Given the large number of different effects and input parameters involved in a modern real-time rendering application, this task can quickly become overwhelming. Recent efforts have therefore focused on automating parts of this process.

4.1. Semi-automatic target identification

The system proposed by Sitthi-amorn *et al.* [SaLY*08b] starts by analyzing the source-code of shaders and identifying possible intermediate computations for reuse. During a training session, the system automatically renders animation sequences while gathering error and performance data on shaders that have been automatically modified to cache and reuse each candidate. The rendering sessions are designed to encompass the range of typical input variation, and are run under a variety of different refresh periods.

Assuming that the input variation is stationary, the authors found empirical models for both the amount of error and the rendering cost associated to reusing each possible intermediate value. These models were later shown to closely match measured data.

The expected error caused by reusing the value f_m of a given intermediate computation *m* over a period of Δn frames can be modelled by a parametric equation:

$$\hat{\epsilon}(f_m, \Delta n) = \alpha_m \left(1 - e^{-\lambda_m(\Delta n - 1)} \right). \tag{4}$$

Parameters α_m and λ_m can be obtained by fitting the model to data gathered in the training session.

Modelling the cost of rendering each pixel requires more work. First, the system solves for an estimate of the average time taken to render a pixel under both cache-hit and cachemiss conditions. Denote these by $\Delta_{hit}(f_m)$ and $\Delta_{miss}(f_m)$, respectively. These values are obtained by solving an overconstrained linear system for $\Delta_{hit}(f_m)$ and $\Delta_{miss}(f_m)$:

$$H_i \Delta_{\rm hit}(f_m) + M_i \Delta_{\rm miss}(f_m) + c = \Delta t_i.$$
⁽⁵⁾

Each equation comes from measurements of different frames i in the training sequence. Here, c is a constant rendering overhead, H_i is the number of hits, M_i the number of misses and Δt_i the time to render frame i.

The average cost of rendering a single pixel can then be modelled as

$$\hat{r}(f_m, \Delta n) = \lambda(\Delta n) \,\Delta_{\text{hit}}(f_m) + (1 - \lambda(\Delta n)) \,\Delta_{\text{miss}}(f_m), (6)$$

where $\lambda(\Delta n) = \mu(1 - 1/\Delta n)$ is an empirical model for the cache hit-rate as a function of Δn , and μ is obtained by fitting this model to the training data.

Using these models, the system allows the developer to specify a target average pixel error. It then automatically selects the shader component that provides the greatest improvement in performance without exceeding the error threshold.

Figure 7 shows the error/performance behaviour associated with caching several different intermediate computations performed by a marble shader. This shader combines a marble-like albedo modelled as five octaves of a 3D Perlin noise function, with a simple Blinn–Phong specular layer.



Figure 7: Trade-off between error and performance associated to caching different intermediate results in a marble shader. Each line shows the effect of varying the refresh period Δn between 2 and 50 frames on each choice of cached intermediate computation. Interesting error thresholds ϵ_i are marked, and the results of which are shown in Figure 8. Original shader runs at 29FPS, as indicated by the dashed line.

Figure 8 shows the results of rendering under each choice of error tolerance, in terms of both quality and performance. As the user selects larger error thresholds, the system reacts by selecting larger portions of the computation for caching (see the payload), eventually including even the view-dependent lighting, at which point undesirable artefacts appear. Nevertheless, substantial performance improvements are possible below an acceptable error threshold (see e_3 running at a 2.8× improvement).

4.2. Reprojection errors and their accumulation

The strategies we use to obtain the values of previous computations (see Section 3) can themselves inject unwanted errors. Although such errors are indirectly modelled by the automatic method described above, here we present a simplified analysis of this specific issue (see [YNS*09] for an alternative, more detailed presentation).

Due to camera and object motions, the corresponding positions of any given surface point in two consecutive frames generally involve non-integer coordinates in at least one of them. Reprojection strategies must therefore *resample* any data that are moved between frames. Bilinear filtering is, by far, the most commonly used resampling strategy in realtime reprojection applications. Mappings between consecutive real-time frames tend to exclude large minifications, making trilinear filtering unnecessary. It is therefore important to understand the impact of bilinear filtering on the quality of reprojected data.

Although analyzing the effect of general motion across multiple frames is impractical, the special case of constant panning motion is easy to describe mathematically,



(ε1) PSNR=67 / FPS=30 (ε2) PSNR=58 / FPS=34 (ε3) PSNR=43 / FPS=82 (ε4) PSNR=33 / FPS=90

Figure 8: Results of selecting different error thresholds in Figure 7. The intermediate value selected for caching (payload) is shown next to the final rendered results (final shading). Higher error thresholds allow for substantial parts of the computation to be cached, leading to better performance at the expense of quality.

particularly in one dimension (other types of motion can be approximated by translation, at least locally).

Assume we have information stored in a frame f_t that we want to resample to time t + 1. Constant panning motion with velocity v can be described by $\pi_{t+1}(p) = p - v$, for every point p and time t. Without loss of generality, assume that the velocity is in [-0.5, 0.5]. The entire resampling operation can be rephrased in terms of the discrete convolution

$$f_{t \to t+1} = f_t * \left[v \ (1-v) \right] \tag{7}$$

$$= f_t * k_v, \tag{8}$$

where we used the notation $f_{t \to t+1}$ to represent the new frame containing only reprojected data. Under our assumptions, the behaviour of reprojection is therefore controlled by the effect of the convolution kernel $k_v = [v \ (1 - v)]$.

For each different velocity v, and for each frequency ω , we compute the amplitude attenuation and the phase error introduced by k_v . Resulting plots are shown in Figure 9, where shaded regions represent values between the extremes. As can be seen from the plots, reprojection through bilinear resampling tends to attenuate and misplace high frequencies. Not visible from the plot is the fact that the problem is particularly extreme when $v = \pm 0.5$ and that it disappears when v = 0 (as expected from the interpolation property).

The effect of repeated resampling can also be analyzed:

$$f_{t \to t+n} = f_{t \to t+n-1} * k_v \tag{9}$$

$$= f_t * \overbrace{(k_v * \cdots * k_v)}^{n \text{ in total}}.$$
 (10)

The trick is to interpret k_v as the probability mass function of a Bernoulli distribution with success probability v.



Figure 9: Amplitude response and phase error associated with translation by linear re-sampling. Note that largest amplitude attenuation and phase error happen for high frequencies.

The distribution has a variance of $\sigma^2 = v (1 - v)$. Repeatedly convolving k_v with itself amounts to computing the sum distribution. By the Central Limit Theorem, this quickly converges to a Gaussian. By the sum property of variance, we have $\sigma_n^2 = n v (1 - v)$. The progressively low-pass nature of repeated resampling then becomes obvious in the formula for the variance.

There are several alternatives to prevent the excessive blur introduced by repeated resampling from causing objectionable rendering artefacts. For example, we can periodically recompute values instead of relying on reprojection. This is, in fact, the approach followed by Sitthi-amorn *et al.* [SaLY*08b] (Section 3.4). Another alternative is to replace bilinear resampling with an alternative strategy that has better frequency properties, such as the one proposed by Yang *et al.* [YNS*09] (Section 5.3). Finally, in the context of computation amortization described in Section 3.5, we can also progressively attenuate the contribution of older frames, thereby limiting the maximum amount of visible blur.

© 2012 The Authors Computer Graphics Forum © 2012 The Eurographics Association and Blackwell Publishing Ltd.

Table 1: Existing approaches that exploit TC in real-time rendering, indexed by applications (rows) and the types of techniques applied (columns), with section numbers of this survey if applicable.

Application	Reverse reprojection (3.1)	Forward reprojection (3.2)	Handling disocclusion (3.3)	Cache refresh (3.4)	Amortized sampling (3.5)	TC target identification (4.1)	Reprojection error (4.2)	Object-space	Post-processing
Pixel shader acceleration (5.1)	[NSL*07]			[SaLY*08b]		[SaLY*08b]			
Multi-pass effects (5.2)	[NSL*07]	[AH93] [CW93] [YWY10] [DRE*10]			[NSL*07]				[HDMS03]
Shading anti-aliasing (5.3)	[YNS*09]			[YNS*09]	[YNS*09]		[YNS*09]		
Shadows (5.4)	[SJW07]				[SJW07] [SSMW09]				
Global Illumination (5.5)	[KTM*10] [MSW10]				[MSW10]			[LSK*07] [REH*11]	
Spatio-temporal upsampling (5.6)	[HEMS10]								
Frame interpolation (5.7)	[YTS*11] [And10]	[DER*10b] [YTS*11]	[And10]						
Non-photorealistic rendering (5.8)		[LSF10] [LSF10]							[BFP*11] [BFP*11]
Level-of-detail (5.9)	[SW08]							[HREB11]	
Streaming (5.10) Online visibility culling (5.11)	[PHE*11]							[FE09] [GKM93] [ZMHI97] [BWPP04] [MBW08]	[FB08]
Temporal perception (5.12)									[DER*10a] [TDR*11]

5. Applications

There are numerous applications in real-time rendering where TC can be exploited to improve the performance and quality. In this section, we aim to summarize the available techniques that follow this direction. Table 1 lists all the relevant approaches that we describe, categorized by the application and the type of techniques applied. Many of these applications are based on image-based reprojection and related approaches (Section 3). Performance and quality studies (Section 4), which were originally discussed in the context of pixel shading acceleration and anti-aliasing, can also be helpful in optimizing RRC-based techniques. In addition, there are several methods that employ an object space or a post-processing type of data reuse, which are also relevant to the topic and discussed in this survey.

5.1. Pixel shader acceleration

One of the direct uses of the RRC is to accelerate expensive pixel-shading computations [NSL*07, SaLY*08a, SaLY*08b]. The basic idea is to bypass part or all of the computation of the original pixel shader whenever there are previous shading results available in the cache, as described in Section 3.4. Figure 4 shows the flow chart of this type of shading acceleration.



Figure 10: Additional examples of shading acceleration using RRC. Each image compares (top) an input pixel shader to (bottom) a version modified to cache some partial shading computations over consecutive frames. The shading error after applying the cache is illustrated in the inset images.

In addition to the marble shader described in Section 4.1, we show two more results of accelerating expensive pixel shaders using the RRC [SaLY*08b]. The first shader is a *Trashcan* environmental reflection shader from ATI's *Toyshop* demo, which combines a simple base geometry with a high-resolution normal map and environment map to reproduce the appearance of a shiny trashcan. The shader combines 25 stratified samples of an environment map using a Gaussian kernel to attenuate aliasing artefacts. In this example, we found that caching the sum of 24 samples of the possible 25 gives the most effective speedup without

introducing too many visible artefacts (see Figure 10 (left) for a comparison). In other words, the modified shader evaluates 24 samples every fourth frame (on average) and evaluates the single sample with the greatest reconstruction weight at every frame. Indeed, this shader is not particularly suited for using TC to accelerate, because all of the calculations depend strongly on the camera position and cached values quickly become stale. Nevertheless, RRC provides a $2.1 \times$ performance improvement at an acceptable level of error.

The second shader computes approximate object-space ambient occlusion at each pixel for a chessboard scene with the king piece moving and the remaining pieces static. The basic idea is to approximate the scene geometry as a collection of discs organized in a hierarchical data structure and stored as a texture. As each pixel is shaded, this data structure is traversed to compute the percentage of the hemisphere that is occluded. This calculation is combined with a diffuse texture and a Blinn-Phong specular layer to produce the final colour. In this particular scene, the ambient-occlusion calculation is carried out by summing the contribution of the king chess piece separately from the other pieces. We found that caching the portion of the ambient-occlusion calculation that accounts for only the static pieces gives the best result. In other words, the contribution of the moving king and the remaining shading are recomputed at every frame. This provides an $8 \times$ speedup for a marginal amount error and is demonstrated in Figure 10 (right). Caching more computations, such as the entire ambient-occlusion calculation, will lead to visible error in the result, although the speedup factor will also be larger ($15 \times$ or more).

5.2. Multi-pass effects

Effects such as motion blur and depth-of-field are most easily understood and implemented as the accumulation of a series of frames, respectively, rendered under slight variations in animation time or camera position, relative to a central frame [HA90]. Although rendering and accumulating multiple frames in order to produce a single output frame may seem prohibitively expensive, the small magnitude of variation in input parameters between each accumulated frame leads to large amounts of coherence between them. This coherence has been successfully exploited in the context of image-based rendering [CW93], ray-traced animation sequences [HDMS03], and more recently in real-time rendering [NSL*07, YWY10]. Imperfections tend to be hidden by the low-pass nature of these effects, leading to images that are virtually indistinguishable from the brute-force results. The savings in rendering cost can be used to either increase quality by raising the number of accumulated frames, or to increase the frame rate for a fixed-quality setting.

The real-time approach proposed in [NSL*07] starts by completely rendering a central frame into a buffer. Then, when rendering the accumulated frames, shading information is obtained from the central frame by reverse reprojection. The extent to which performance is improved depends on the relative cost between rendering the central frame (geometry + shading) and rendering each accumulated frame (geometry + cache-lookup). This is because reverse reprojection requires rasterizing the geometry of each accumulated frame (see Section 3.1). Improvements are therefore limited when geometry is complex and shading is relatively simple. Yu *et al.* [YWY10] proposed to use forward reprojection (Section 3.2) in order to decouple this overhead from geometry complexity. They also apply a blurring pass to the reprojected frames before accumulation so that the undersampling and disocclusion artefacts are attenuated.

Another rendering scenario that is closely related to depthof-field is stereographic rendering. Two views are rendered from the same scene, one from the viewpoint of each eye of a virtual observer. Then, one of many different methods is used to expose each of the user's eyes to the corresponding image (e.g. shutter glasses and polarization filters), leading to the perception of depth. Stereographic rendering has recently gained increased attention given the success of 3D cinematographic productions as well as the increased availability of 3D-capable consumer hardware (TV sets, portable video-game consoles, etc.).

One way to avoid the doubling of cost-per-frame that would result from the brute-force approach to stereographic rendering is to instead render only one frame from the stereo pair and then warp it to produce the other frame. This is a well-established idea that was successfully used in the context of stereographic ray-tracing [AH93] (where rendering cost was extremely high) and in stereographic head-tracked displays [MB95] (where warping was used to efficiently update a previously rendered stereo pair to compensate for user head movements).

Since per-pixel depth information is a natural by-product of real-time rendering, generating the mapping between two stereo views is particularly easy. The challenges are in the design of an efficient warping procedure that adapts to sharp features and attenuates any artefact resulting from surface points that are only visible from one of the viewpoints.

One way to perform this operation is to rely on an adaptive warping grid [DRE*10] (see Section 3.2) to transform one view into another. Didyk *et al.* further proposed to exploit TC by analyzing the camera movement from one frame to the next. Depending on the camera movement and the previously computed frame, it can be more advantageous to render and then warp either the left or the right eye view. For example, imagine a panning motion from left to right. Here, a right-eye view in frame i might be very close to a left-eye view in frame i + 1. Consequently, it makes sense to render the right eye view in frame i + 1. The rendered frame and the previous are then warped to produce a left-eye view for frame i + 1. In particular, for a static camera and scene, the result is indistinguishable from a two-view rendering.



Figure 11: Sampling from multiple sub-pixel buffers. To properly reconstruct the quadrant value, Yang et al. [YNS*09] use non-uniform blending weights defined by a tent function centred on the quadrant being updated. (a) In the absence of local motion, only the correct pixel has nonzero weight in the tent, so no re-sampling blur is introduced. (b) For a moving scene, the samples are weighted using the tent function, and higher weights are given to samples closer to the desired quadrant centre to limit the amount of blur.

5.3. Shading anti-aliasing

One of the direct applications of amortized sampling (Section 3.5) is to supersample procedural shading effects, which usually contain high-frequency components that are prone to aliasing artefacts. By accumulating jittered samples generated in previous frames using amortized sampling, the extra frequency bands can be effectively suppressed. However, supersampling usually requires a small exponential smoothing factor α in order to gather sufficient samples. This has the undesired side effect that the running estimate can be overblurred because of excessive repeated resampling of the cache (Section 4.2).

Yang *et al.* [YNS*09] proposed to keep a higher resolution (2×2) running average in order to counteract this overblurring artefact. To reduce the overhead of maintaining such a high-resolution buffer, they store the 2×2 quadrant samples of each pixel into four sub-pixel buffers $\{b_k\}, k \in \{0, 1, 2, 3\}$ using the interleaved sampling scheme. Each sub-pixel buffer is screen sized and manages one quadrant of a pixel. These sub-pixel buffers are updated in a round-robin fashion, i.e. only one per frame.

Reconstructing a sub-pixel value from the four sub-pixel buffers involves more work. Note that in the absence of scene motion, these four sub-pixel buffers effectively form a higher resolution framebuffer. However, under scene motion, the sub-pixel samples computed in earlier frames reproject to offset locations. Conceptually, Yang *et al.* [YNS*09] forward reproject all the previous samples into the current frame and compute a weighted sum of these samples using a tent kernel, as indicated in Figure 11. This effectively reduces the contribution of distant samples and limits the amount of blur



Figure 12: Comparison between no anti-aliasing, amortized supersampling with viewport size cache (Amort1×), amortized supersampling with improved 2×2 sub-pixel buffers (Amort4×) and the ground-truth reference result for a horse-checkerboard scene [YNS*09]. The 4× 'still' image (without animation) approaches the quality of the reference result, whereas the animated result provides an acceptable approximation without overblurring.

introduced. It also correctly handles both static and moving scenes simultaneously.

In addition to the higher resolution buffer, empirical methods are used to estimate reconstruction errors as well as the amount of signal change in real time, and limit α accordingly such that a minimum amount of refresh is guaranteed. The reconstruction error is estimated by deriving an empirical relationship between the fractional pixel velocity **v**, α and the error. Signal change, on the other hand, is estimated by a smoothed residual between the aliased sample and the history value. The user sets thresholds for both errors, and the bounds for α are computed based on the error values.

Figure 12 shows the result of applying amortized sampling to anti-aliasing a horse-checkboard scene, which includes an animated wooden horse galloping over a marble checkered floor. The result using 2×2 sub-pixel buffers shows significant improvement over regular amortized sampling ($1 \times$ viewport-sized cache), with only a minor sacrifice of speed. In fact, the PSNR shows that this technique offers better quality than conventional 4×4 stratified supersampling, which runs at a six times lower frame rate.

5.4. Shadows

Shadows are widely acknowledged to be one of the global lighting effects with the most impact on scene perception. They are perceived as a natural part of a scene and give important cues about the spatial relationship of objects. The field of shadow algorithms is vast and many different methods



Figure 13: If the rasterization of the shadow map changes (here represented by a right shift), the shadowing results may also change. On the left, three fragments are in shadow, while on the right, five fragments are in shadow. This results in flickering or swimming artefacts in animations.

exist. Several surveys [HLHS03, SWP11], courses [EASW09, EASW10], and books [ESAW11] illustrate numerous approaches to address this important problem.

Due to its speed and versatility, shadow mapping is one of the most used real-time shadowing approaches. The idea is to first create a depth image of the scene from the point of view of the light source (shadow map). This image encodes the front between lit and unlit parts of the scene. On rendering the scene from the point of view of the camera, each fragment is transformed into this space. Here, the depth of each transformed camera fragment is compared to the respective depth in the shadow map. If the depth of the camera fragment is nearer, it is considered lit, otherwise it is in shadow (see Figure 13).

5.4.1. Pixel-correct shadows

The most concerning visual artefacts of shadow mapping originate from aliasing due to undersampling. The cause for undersampling is, in turn, closely related to the rasterization that is used to create the shadow map itself. Rasterization samples primitives on a regular grid. Each fragment is centred on one of these samples, but is only correct exactly at its centre. If the viewpoint changes from one frame to the next, the regular grid sampling of the new frame is likely to be completely different than the previous one. This frequently results in artefacts, especially noticeable for thin geometry and the undersampled portions of the scene called *temporal aliasing*.

This is especially true for shadow maps. Due to shadow map focusing, a change in the viewpoint from one frame to the next also changes the regular grid sampling of the shadow map. Additionally, the rasterized information is not accessed in the original light space where it was created, but in eye space, which worsens these artefacts. This frequently



Figure 14: Shadow adaption over time of an undersampled uniform shadow map after 0 (top-left), 1 (top-middle), 10 (top-right), 20 (bottom-left), 30 (bottom-middle) and 60 (bottom-right) frames.



Figure 15: Light-space perspective shadow mapping [WSP04] (left) gives good results for a shadow map resolution of 1024^2 and a view port of 1680×1050 , but temporal reprojection (middle) can still give superior results because it uses shadow test confidence, defined by the maximum norm of shadow map texel centre and current pixel (right).

results in temporal aliasing artefacts, mainly flickering (See Figure 13).

The main idea in [SJW07] is to jitter the viewport of the shadow map differently in each frame and to combine the results over several frames, leading to a higher effective resolution. Figure 14 shows the gradual refinement after accumulating results from multiple frames.

Exponential smoothing as described in Section 3.5 is employed here on the shadow map tests $s_t[\mathbf{p}]$. This serves a dual purpose. On the one hand, temporal aliasing can be reduced by using a small smoothing factor α . On the other hand, the shadow quality can actually be made to converge to a pixel-perfect result by optimizing the choice of the smoothing factor.

The smoothing factor α allows balancing fast adaption on changing input parameters against temporal noise. With a larger smoothing factor, the result depends more on the new shadow results from the current frame and less on older frames and vice versa. To this end, the smoothing factor is determined per-pixel according to the *confidence* of the shadow lookup. This confidence is defined to be higher if the lookup falls near the centre of a shadow map texel, since only near the centre of shadow map texels, it is very likely that the sample actually represents the scene geometry (see Figure 15). In this paper, the maximum norm of the current



Figure 16: *Light sampling with 1, 2, 3 and 256 shadow maps (left to right).*

pixel \mathbf{p} and the shadow map texel centre \mathbf{c} is used to account for this

$$\operatorname{conf} = \left(1 - \max\left(\left|\mathbf{p}_{x} - \mathbf{c}_{x}\right|, \left|\mathbf{p}_{y} - \mathbf{c}_{y}\right|\right) \cdot 2\right)^{m}, \quad (11)$$

but other norms could be used as well. The parameter m defines how strict this confidence is applied. m < 4 results in fast updates where most shadow map lookups of the current frame have a big weight and the resulting shadow has noisy edges. m > 12 results in accurate but slow updates where most lookups from the current frame have small weight.

The authors found out that m should be balanced with camera movement. When the camera moves fast, m can be small because noise at the shadow borders is not noticed. Only for a slowly moving camera or a still image are higher values of m necessary. This is motivated by the human visual system, which tends to integrate over motion, thereby allowing for noisier edges when strong movement is present. This confidence can now be directly used in the exponential smoothing formula (see Section 3.5)

$$f_t[\mathbf{p}] \leftarrow (\operatorname{conf})s_t[\mathbf{p}] + (1 - \operatorname{conf})f_{t-1}(\pi_{t-1}(\mathbf{p})).$$
 (12)

5.4.2. Soft shadows

In reality, most light sources are area light sources, and hence most shadows exhibit soft borders. *Light-source sampling* [HH97] creates a shadow map for every sample (each on a different position on the light source) and calculates the average (= soft shadow) of the shadow map test results s_i for each pixel (see Figure 16). Therefore, the soft shadow result from *n* shadow maps for a given pixel **p** can be calculated by

$$\psi_n(\mathbf{p}) = \frac{1}{n} \sum_{i=1}^n s_i(\mathbf{p}).$$
(13)

The primary problem here is that the number of samples (and therefore shadow maps) to produce smooth penumbrae is huge. Therefore, this approach is inefficient in practice. Typical methods for real-time applications approximate



Figure 17: Left side: PCSS 16/16; Overlapping occluders (upper row) and bands in big penumbras (lower row) are known problematic cases for single-sample approaches. Right side: soft shadows exploiting TC.

an area light by a point light located at its centre and use heuristics to estimate penumbrae, which leads to soft shadows that are not physically correct (see Figure 17, left). Overlapping occluders can lead to unnatural-looking shadow edges, or large penumbrae can cause single-sample softshadow approaches to either break down or become very slow.

One observation is that the shadow sampling can be extended over time. It is, for example, possible to change the sampling pattern on the source in each frame, thereby trading aliasing artefacts with less objectionable random noise. This is particularly easy to achieve for symmetric light sources [ED07b, SEA08]. More generally, light source area sampling can be formulated in an iterative manner by evaluating only a single shadow map per frame [SSMW09]. Reformulating Equation (13) gives

$$\psi(\mathbf{p}) = \frac{s(\mathbf{p}) + \Sigma(\mathbf{p})}{n(\mathbf{p}) + 1} \qquad \Sigma(\mathbf{p}) = \sum_{i=1}^{n(\mathbf{p})} s_i(\mathbf{p}), \quad (14)$$

where $s(\mathbf{p})$ is the hard shadow-map result for the current frame and pixel and $n(\mathbf{p})$ is the number of shadow maps evaluated until the previous frame for this pixel. Note that now *n* depends on the current pixel because depending on how long this pixel has been visible, a different number of shadow maps may have been evaluated for this pixel. The calculation of this formula is straightforward if $n(\mathbf{p})$ and $\Sigma(\mathbf{p})$ are stored in a buffer (another instance of the RRC: see Section 3.1). With this approach, the soft shadow improves from frame to frame and converges to the true soft shadow result if pixels stay visible 'long enough' (see Figure 18, upper row).

In practice, this can result in temporal aliasing for small *n*. Care has to be taken in order to properly manage those



Figure 18: Convergence after 1,3,7,20 and 256 frames; upper row: sampling of the light source one sample per frame; lower row: soft shadows with TC.



Figure 19: Structure of the soft shadows with TC algorithm.

cases. When a pixel becomes newly visible and therefore no previous information is available in the RRC, a fast singlesample approach (PCSS with a fixed 4×4 kernel) is employed to generate an initial soft shadow estimation for this pixel. For all other *n*, the expected standard error is calculated and if it is above a certain threshold (expected fluctuation in the soft shadow result in consecutive frames), a depthaware spatial filter is employed to take information from the neighbourhood in the RRC into account (see Figure 19). This approach largely avoids temporal aliasing and can be nearly as fast as hard shadow mapping if all pixels have been visible for some time and the expected standard error is small enough (see Figures 18 and 17).

5.5. Global illumination

It is a major goal of real-time research to achieve plausible (and in the long run, physically correct) global illumination. In this section, we present several techniques that explore TC in an attempt to approximate global illumination effects in real time. Many techniques can be found in the excellent survey by Damez *et al.* [DDM03]. Nonetheless, the focus is often on offline solutions or it is assumed that knowledge of subsequent keyframes is available. For interactive rendering, this is not always achievable and specialized solutions are needed. In this context, it is difficult to exploit TC on current GPUs, which is in the focus of our overview.

The radiance emitted from point p into direction ω can be described by the rendering equation [Kaj86, ATS94]

$$L(\mathbf{p},\omega) = L_e(\mathbf{p},\omega) + \frac{1}{\pi} \int_{\Omega} f_r(\mathbf{p},\omega',\omega) L_i(p,\omega')(\mathbf{n}_{\mathbf{p}}\cdot\omega')d\omega'.$$
 (15)

Ω denotes the space of all hemispherical directions, L_e is the self emission, f_r is the *bidirectional reflectance distribution function* (BRDF), L_i is the incident light from direction ω' and n_p is the surface normal.

Global illumination algorithms often use Monte-Carlo sampling to evaluate this multi-dimensional integral in a feasible way. We can exploit TC between consecutive frames, e.g. by spreading the evaluation of the integral over time.

5.5.1. Screen-space ambient occlusion

Ambient occlusion [CT81] is a cheap but effective approximation of global illumination which shades a pixel with the percentage of the hemisphere that is blocked. It can be seen as the diffuse illumination of the sky [Lan02]. Ambient occlusion of a surface point \mathbf{p} is computed as

$$AO(\mathbf{p}, \mathbf{n}_{\mathbf{p}}) = \frac{1}{\pi} \int_{\Omega} V(\mathbf{p}, \omega') \left(\mathbf{n}_{\mathbf{p}} \cdot \omega' \right) \, d\omega'.$$
(16)

The (inverse) visibility function V was originally defined as a binary function where $V(\mathbf{p}, \omega') = 1$ if the visibility in this direction is blocked by an obstacle, 0 otherwise. However, other choices for V (e.g. an exponential falloff based on distance) give visually more pleasing (i.e. smoother) results.

Screen-space ambient occlusion (SSAO) methods [Mit07] sample the frame buffer as a discretization of the scene geometry. These methods are of particular interest for real-time applications due to the fact that the shading overhead is mostly independent of scene complexity, and several variants of SSAO have been proposed since [FC08, BSD08, SKUT*10]. We assume that any SSAO method can be written as an average over contributions *C* depending on a series

of samples s_i:

$$SSAO_n(\mathbf{p}) = \frac{1}{n} \sum_{i=1}^n C(\mathbf{p}, \mathbf{s}_i), \qquad (17)$$

where a typical contribution function for a single SSAO sample can be

$$C(\mathbf{p}, \mathbf{s}_i) = V(\mathbf{p}, \mathbf{s}_i) \max(\cos(\mathbf{s}_i - \mathbf{p}, \mathbf{n}_p), 0).$$
(18)

 \mathbf{s}_i is an actual sample point around \mathbf{p} , and $V(\mathbf{p}, \mathbf{s}_i)$ is now a binary visibility function that is resolved by evaluating the depth test for s_i .

Reverse reprojection allows us to cache and reuse previously computed SSAO samples. The properties of SSAO (relatively low-frequency, independence from light-source, local support of the sampling kernel) are beneficial for using TC, as it was already demonstrated in commercial games [SW09]. In the following, we discuss the temporal SSAO (TSSAO) method of Mattausch et al. [MSW10], who focus on improving the accuracy and visual quality of SSAO for a given number of samples per frame, and introduce an invalidation scheme that handles moving objects well.

A comparison of conventional SSAO with TSSAO is shown in Figure 20. The noisy appearance of a coarse SSAO solution that uses only a few samples (image a) can be improved with a screen-space spatial discontinuity filter. However, the result of this operation can be quite blurry (image b). As long as there is a sufficient history for a pixel, TSSAO produces smooth but crisp SSAO without depending on heavy post-processing (image c).

Integration over time. In frame t, a new contribution C_t is calculated from k new SSAO samples.

$$C_t(\mathbf{p}) = \frac{1}{k} \sum_{i=j_t(\mathbf{p})+1}^{j_t(\mathbf{p})+k} C(\mathbf{p}, \mathbf{s}_i),$$
(19)

where $j_t(\mathbf{p})$ counts the number of unique samples that have already been used in this solution. The new contribution is combined with the previously computed solution

$$SSAO_{t}(\mathbf{p}) = \frac{w_{t-1}(\mathbf{p}_{t-1})SSAO_{t-1}(\mathbf{p}_{t-1}) + kC_{t}(\mathbf{p})}{w_{t-1}(\mathbf{p}-1) + k} , (20)$$

$$w_t(\mathbf{p}) = \min(w_{t-1}(\mathbf{p}_{t-1}) + k, w_{max}).$$
(21)

The weight w_{t-1} represents the number of samples that have already been accumulated in the solution, until w_{max} has been reached. The solution converges very quickly, and this predefined maximum controls the refresh rate and ensures that the influence of older contributions decays over time.

Note that for TSSAO, spatial filtering of the result to reduce noise only has to be applied in regions where the solution has not sufficiently converged. This is done by shrinking

Figure 20: SSAO without TC using 32 samples per pixel

with (a) a weak blur, (b) a strong blur (both 23 FPS) and (c) temporal SSAO using 8-32 samples (initially 32, 8 in a converged state) (45 FPS). (d) Reference solution using 480 samples (2.5 FPS). The scene has 7M vertices and runs at 62 FPS without SSAO.

the screen-space filter support proportionally to the convergence w_n/w_{max} . The results of the filtering can be further improved by making it convergence aware, i.e. assigning higher weights to sufficiently converged filter samples.

Detecting changes. Special attention must be paid to the detection of cache misses (i.e. pixels with an invalid SSAO solution). A cached value of a pixel is invalid if either one of the following three conditions has occurred: 1) a disocclusion of the current pixel, 2) the pixel was previously outside the frame buffer or 3) a change in the sample neighbourhood of the pixel. Case 1) and case 2) can be handled like conventional cache misses as described previously in Section 3.3. However, it is important to additionally check for case 3), because nearby changes in the geometry can affect the shading of the current pixel.





Figure 21: The distance of **p** to sample point \mathbf{s}_2 in the current frame differs significantly from the distance of \mathbf{p}_{t-1} to $\mathbf{s}_{2_{t-1}}$ in the previous frame; hence, it can be savely assumed that a local change of geometry occurred, which affects the shading of **p**.

The authors use sampling to check the neighbourhood of a pixel for changes in the AO value. In practice, this neighbourhood test does not introduce additional lookups, as the available set of samples used to compute $C_t(\mathbf{p})$ can be reused. It is an important observation that a contribution $C(\mathbf{p}, \mathbf{s}_i)$ only varies if the configuration of a sample position \mathbf{s}_i relative to \mathbf{p} changes (e.g. the AO on a rotating object only changes in the vicinity of other objects). Hence, as illustrated in Figure 21, the algorithm uses the distance differences

$$\delta(s_i) = ||\mathbf{s}_i - \mathbf{p}| - |\mathbf{s}_{i_{t-1}} - \mathbf{p}_{t-1}||$$
(22)

as a measure of change. The change in the surface angle between s_i and p could have been used additionally, but it would have caused an additional overhead. It is sufficient to use those samples that lie in front of the tangent plane of p for the neighbourhood test, since only those samples actually modify the shading.

Smooth invalidation. Consider, for example, a slowly deforming surface, where the SSAO will also change slowly. In such a case, it is not necessary to fully discard the previous solution. Instead, the authors introduce a new continuous definition of invalidation that takes a measure of change into account. This measure of change is given by $\delta(s_i)$ at validation sample position s_i , as defined in Equation (22). In particular, the algorithm computes a *confidence* value **conf**(s_i) between 0 and 1. It expresses the degree to which the previous SSAO solution is still valid:

$$\operatorname{conf}(\mathbf{s}_{i}) = 1 - \frac{1}{1 + S\delta(\mathbf{s}_{i})}.$$
(23)



Figure 22: Moving dragon model using no invalidation (left, causing severe artefacts in the shadow), and using an invalidation factor set to a proper value (right, no artefacts).

The invalidation factor *S* is a parameter which controls the smoothness of the invalidation. The overall confidence conf(p) in the previous SSAO solution is given by $min(conf(s_0), ..., conf(s_k))$. This value is used to attenuate the weight w_t given to the solution of the previous frame in Equation (21). Figure 22 shows the effect of the invalidation and smooth invalidation factor on a scene with a moving object.

5.5.2. Instant radiosity

Instant radiosity [Kel97] is a hardware-friendly global illumination method that computes so-called virtual point lights (VPLs) along the intersections of a light path with a surface and uses them for indirect scene illumination. The visibility is resolved by computing an individual shadow map for each VPL. The shadow-map computation is also the main bottleneck of the algorithm, as it requires sampling the scene many times for a reasonable number of VPLs. This drawback prevents real-time frame rates for the original version of this algorithm. In the following, we will demonstrate how to use object-level and pixel-level TC to improve the performance and visual quality of this important global illumination algorithm.

Incremental instant radiosity. By reusing VPL visibility over time, Laine *et al.* [LSK*07] proposed a method that exploits object-level TC to reach real-time frame rates. For the sake of performance, this algorithm only computes first-bounce indirect illumination, which is sufficient in most cases. Even so, hundreds of shadow maps are needed for convincing global illumination. In order to keep the number of VPL computations per frame feasible for real-time purposes, this algorithms reuses the valid VPLs from the previous frame and recomputes only a *small budget* of invalid shadow maps in a frame. A VPL stays valid if it is within the light frustum and is not occluded from the light source (which is tested with a ray caster). The algorithm is visualized in Figure 23.

The main task of this algorithm is to incrementally maintain a good distribution of the VPLs during consecutive frames. Assuming a 180° spotlight, the algorithm uses the fact that a cosine-weighted distribution on a hemisphere



Figure 23: (Left) Instant radiosity shoots paths from the light source, and creates VPLs at the intersection with geometry. (Middle) Using shadow maps, the visibility of each VPL and their contribution to the current image is determined. (Right) TC: When the view point or light source moves, one of the VPLs becomes invisible from the light source, and all the others are reused. Image courtesy of Samuli Laine.



Figure 24: An uniform distribution on the unit disc corresponds to a cosine-weighted distribution on a hemisphere. The VPL management aims to keep the uniformity of the VPLs on the unit disc while recomputing a budget of VPLs per frame. Image courtesy of Samuli Laine.

corresponds to a uniform distribution on a disc (as shown in Figure 24). In order to manage the VPL distribution on the unit disc, the algorithm creates a 2D Delaunay triangulation. To choose the best position for new VPLs, the algorithm minimizes *dispersion*, which is computed as the radius of the largest empty circle that contains no sample points. In case of omni-directional light sources, the algorithm operates on the unit sphere instead of the unit disc.

Note that the algorithm captures changes in the scene with a certain latency, and shadows cast from dynamic objects are not supported. The authors report a speedup from 1.4 to 6.8 for different scenes and resolutions. In their tests, they fixed the number of VPLs to 256 and the recomputation budget to 4–8 VPLs.

Imperfect shadow maps. Based on the observation that coarse visibility is sufficient for low-frequency global illumination, Ritschel *et al.* [RGK*08] significantly accelerate the VPL generation for instant radiosity. They use a point-based scene representation and distribute these points among the VPLs to generate so-called imperfect shadow maps. While each shadow map is sampled with only a coarse subset of scene points, holes can be closed with a pull–push algo-

rithm. This method allows hundreds of shadow map-based visibility queries per frame in at least interactive time.

However, even such a large number of queries is insufficient to avoid typical undersampling artefacts, e.g. resulting in flickering between frames if the VPLs are recomputed. In order to improve the visual quality and reduce these artefacts, it is straightforward to combine the imperfect shadow map approach with temporal reprojection.

Recently, the undersampling issues were addressed to some extent by relying on a view-adaptive solution [REH*11]. The idea is to update a part of the point-based scene representation for each frame, thereby ensuring more precision where surfaces visible to the observer are affected. Also, the VPL selection and placement is optimized by proposing a novel scheme. By selecting appropriate VPLs from a large set of potential VPLs depending on their estimated impact on the visible scene from the observer, much higher fidelity is achieved. Further, by employing a novel VPL-placement scheme for dynamic light sources, they tend to move in a more continuous way over continuous surfaces. Therefore, the temporal consistency of indirect illumination is significantly improved.

The main problem of using TC for global illumination is the global nature of changes of the lighting conditions and the scene configuration—some trade-off between smoothing and correctness is inevitable and a satisfactory general solution is hard to find. Knecht *et al.* [KTM*10] chose to use a confidence value instead of a binary threshold for invalidation. In particular, the confidence in reusing a previous solution is guided by the amount of change of a pixel between the previous and current frame. To this end, they introduce a couple of parameters:

$$\begin{aligned} \epsilon_{pos} &= ||(x_t - x_{t-1}; y_t - y_{t-1}; d_t - d_{t-1}) \mathbf{w}_{\mathbf{p}}||, \\ \epsilon_{norm} &= (1 - n \cdot n_{prev}) w_n, \\ \epsilon_{ill} &= saturate(||I_t - I_{t-1}||^3) w_i, \\ conf &= saturate(1 - \max(\epsilon_{pos}; \epsilon_{norm}; \epsilon_{ill})) c_B. \end{aligned}$$
(24)

The three ϵ terms compute three distance values of screenspace position and depth, normal and illumination value, respectively. The weights $\mathbf{w}_{\mathbf{p}}$, w_n and w_i are highly scenedependent and require fine-tuning by the user. The final confidence is computed as the maximum of these measures multiplied by some base confidence c_B , and is then used as the weight of a standard exponential smoothing operation (see Section 3.5).

As can be seen in Figure 25, TC improves the quality and reduces the noise caused by the undersampling. The quality improvement is most visible during animations, where distracting flickering artefacts due to varying VPL positions can be avoided using TC. Due to the low-frequency nature of indirect illumination, the artefacts caused by moving light sources and animated objects are not very distracting in the general case (they are similar to motion blur).



Figure 25: Imperfect shadow maps still show some artefacts with 256 VPLs, which can be smoothed out using TC. Image courtesy of Martin Knecht.

5.6. Spatio-temporal upsampling

In addition to TC, also spatial coherence may exist within shading signals (e.g. low-frequency diffuse shading). Herzog *et al.* [HEMS10] proposed a spatio-temporal upsampling technique that exploits temporal and spatial redundancy. Strong temporal changes (e.g. moving lights) are handled with spatial upsampling, while coherency is exploited to ensure a high-quality convergence via temporal upsampling. Such spatio-temporal filtering is often applied for video restoration [Tek95, BM05] and can also be used to suppress aliasing artefacts [Shi95].

The basic approach of spatio-temporal upsampling follows a joint- or cross-bilateral upsampling [TM98, SB95, ED04, PSA*04, KCLU07, YSL08] scheme:

$$f_{t}(\mathbf{p}) = \frac{1}{\sum w^{s}w^{t}w^{f}} \sum_{q=0}^{T} \sum_{j \in \mathcal{N}[\mathbf{p}_{q}]} w^{s}(\mathbf{p}_{q}, j) w^{t}(\mathbf{p}_{q}, j) w^{f}(q) f_{t-q}^{l}(\hat{j}),$$
(25)

where \mathcal{N} describes a spatial neighbourhood around a pixel and q is an index that indicates the frames over time. Hence, the double summation takes space and time into account. Weight w^s computes the world-space distance and similarity of samples based on surface properties such as normals or material indices. Weight w^t is a binary occlusion test, checking whether the reprojected pixel $\mathbf{p}_q = \pi_{t-q}(\mathbf{p})$ is actually visible in the corresponding frame. Weight w^f describes a temporal fadeout that reduces the influence of older pixels. The term $\frac{1}{\sum w^s w^t w^f}$ normalizes the weighting coefficients. The term f_{t-a}^{l} are low-resolution frames that were created using an interleaved pixel refresh at time t - q and consequently, \hat{j} is the index of the nearest pixel in the low-resolution image that corresponds to pixel *j*. While, in theory, it seems that many previous frames have to be kept in memory, choosing exponential weights allows for an accumulation in a single history buffer [HEMS10].

Nonetheless, when involving samples from previous frames, it is important to detect which pixel shading values are still useful for the current frame. For a fast moving light, for example, shadows might change their location and easily pollute a temporal integration. In order to capture these effects, Herzog *et al.* proposed to examine the temporal gradient of the previously constructed frame and the only spatially upsampled current frame. If the gradient is low, more confidence is given to temporal weights, if not, the algorithm favours spatial upsampling techniques to produce the final high-quality version of the current frame. The intuition is simple. If a region of an image changed little over time, it is useful to exploit more samples from previous frames, whereas if strong changes occurred, older values should be considered unreliable. In order to make this solution more robust to outliers, a temporal smoothing is applied to the gradient.

Each low-resolution shading frame f_{t-q}^{l} is produced using interleaved sampling, meaning that the camera is changed to ensure that when putting all low-resolution images together, one can actually produce a complete high-resolution rendering without artefacts. In practice, the temporal fadeout makes it impossible to ensure a perfect match, but the quality is still higher than for spatial or temporal upsampling alone.

5.7. Frame interpolation

Frame interpolation is widely applied in video encoding and uses temporal redundancy to allow for a better compression behaviour. We will investigate compression and streaming briefly in Section 5.10. Here, we analyze a second reason to employ frame interpolation strategies: hold-type blur.

Nowadays, hold-type displays, such as LCD screens, show an image over a longer period of time instead of flashing it on the screen. The resulting perceptual effects are very interesting. In fact, moving content is perceived blurred because the eve tracks the content over the screen. During the eve motion, the image content stays partly constant (due to an insufficient frame rate), which leads to an integration of the image on the retina (not unlike motion blur) [KV04]. For a long time, a lot of the blur perception was wrongly attributed to the display's response time, but Pan et al. [PFD05] showed that only 30% of the perceived blur are a consequence of it. The remaining 70% are mostly a result of hold-type blur. Especially for low frame rates, this effect can have dramatic consequences and reduce the image quality drastically [Jan01], but even reaction times decrease and task performance is reduced [DER*10b].

Modern TVs try to optimize image quality by employing interpolation schemes [FPD08]. While an accurate interpolation and matching of content over time can become very difficult for a TV set because optical flow is challenging to compute robustly, a rendering context offers many advantages since the problem is actually much simpler. It is possible to derive accurate velocity and geometric information from a scene by simply rendering it into a buffer. Thereby, one can avoid approximate image-based estimates. TV sets are still successful in many cases because, at high frame rates, the precision of our perception is reduced. Consequently, intermediate images do not have to exhibit the same quality as key frames.

Didyk et al. [DER*10b] introduced a method that builds upon the observation that intermediate frames can be of lower quality and exploit the effect algorithmically. Their approach produces a high frame rate sequence that is then directly fed unaltered to a high-refresh LCD screen. They rely on the key observation that the human visual system spreads high frequencies of one frame over succeeding blurred frames if a sufficiently high frame rate is reached [TV05]. Therefore, they can hide potential artefacts in warped frames. More precisely, they extrapolate a given image and blur all parts of the warped image that might potentially exhibit a reduced image quality. The frequencies that are lost by the blurring process in the extrapolated frames can be compensated for in the unwarped original frame. In the affected regions, the amplitude of the high frequencies is increased according to the blur that is applied to the successive frames. Because artefacts are hidden by the blur, a very cost-effective grid warping strategy can be used. This grid is deformed by velocity vectors that are directly extracted from the scene, and a snapping process ensures that the main discontinuities are respected. The technique is successful enough to enable the addition of two intermediate frames. In other words, a 40 Hz sequence can be transformed into a 120 Hz output that is almost indistinguishable from an actually rendered 120 Hz sequence, which was confirmed by a user study.

Andreev [And10] also proposed a temporal upsampling scheme, but makes use of an approximate image-based warping strategy. He targets only a single in-between frame to successfully transform 30 Hz sequences to 60 Hz. The idea is to rely again on a frame extrapolation, but to further separate static and dynamic content. Static elements are usually well handled by warping strategies, but dynamic objects can hide-and when warped, unveil-important parts of the scene. Consequently, holes can appear in the extrapolated frames. Andreev proposes to copy static pixel patches from the neighbourhood to fill up these holes. The dynamic content is then added on top of the final shot. The algorithm is useful and well-adapted for current game consoles (XBox, PS3). It finds application in several shipping game titles, which shows its practical relevance. Andreev also explores a solution that interpolates between two frames for more accurate results. He reports that it requires more computational resources and adds an extra frame of latency, which is unsuitable to their games.

Concurrent with Andreev's talk [And10], Yang *et al.* [YTS*11] introduced a method that interpolates a pair of consecutive rendered frames. They proposed a new image-based reprojection strategy as described in Section 3.2, which is used to retrieve the information from both rendered frames for each interpolated frame. The method avoids rasterizing scene geometry altogether at these intermediate frames and is very efficient. With their implementation, using the fu-



Figure 26: *Examples of stylizing a frame from a rendered* 3D *animation of a tank scene (left) and a 3D animation of a lizard with a still photograph in the background (right).*

ture rendered frame only introduces a small amount of lag, and their user studies show that the effect of this lag was minor. The method yields substantial performance improvements to both vertex-bound and pixel-bound scenes, as well as multi-pass rendering techniques, such as deferred shading and motion blur.

5.8. Non-photorealistic rendering

Real-time reprojection has also been used by a nonphotorealistic rendering (NPR) system that converts animated scenes to artistic brush-stroke renderings of different styles [LSF10]. Computing a new set of NPR strokes from scratch in each frame of an animation sequence results in significant flickering artefacts. Instead, the algorithm maintains TC by treating brush strokes as particles and advecting the vast majority of them according to the scene motion.

In order to advect brush strokes, the algorithm generates a buffer that stores per-pixel forward motion vectors for the animated scene. This buffer can be efficiently computed on the GPU by using reprojection to calculate the forward motion vector from frame t - 1 to frame t in the vertex shader. The motion vector is interpolated by the hardware and provided as input to the pixel shader. Much like traditional reprojection, the pixel shader homogenizes the motion vector and then outputs the result to the render target in the clip space of frame t - 1. Finally, each brush stroke particle uses this motion vector buffer to forward reproject its position from frame t - 1 to frame t. Figure 26 shows examples of synthetic scenes rendered with this system.

Recently, solutions also focused on different ways of attaching brush strokes to extracted feature curves. SLAM textures [BCGF10] (self-similar line artmaps) are a means to produce a multi-resolution representation of a stylized line pattern. Basically, the stylized pattern is self-similar on several resolution levels. This property is assured by performing a suitable texture synthesis algorithm that derives smooth transitions from a simple pattern to a more detailed higher resolution version. During rendering, the appropriate detail level can be chosen from the SLAM representation. Unfortunately, when moving elements over time, these strokes, while maintaining a coherent look, may slide over the surface as the extracted feature lines on the mesh, and hence, their parametrization may change. The approach suggests to keep similar texture coordinates over time by reprojecting the parametrization when computing the next frame.

Kalnins *et al.* [KMM*02, KDMF03] avoid the use of specialized line patterns and instead proposed to optimize the line parametrization itself. They also focus on temporally consistent textured lines and aim at minimizing the mentioned sliding or stretching that would occur for naive parametrizations. By tracking particle-like curve elements on the surface, they enable a certain continuity of the rendering. Nonetheless, topological changes of the extracted feature curves cannot be easily parametrized as they are inherently inconsistent. By analyzing a defined animation sequence, one can detect topological events using a space-time contour surface [BFP*11]. By coupling cuts and merges, discontinuities are reduced and the final parametrization is optimized via a least-squares fit that optimizes texture sliding and stretch.

Kass and Pesare [KP11] introduced a method for generating coherent noise for NPR applications. Their method achieves the illusion of random variation in the noise from any given viewpoint in an animation sequence while remaining temporally coherent. To preserve coherence, they employ a recursive filter and handle disoclusion by comparing reprojected depth values much like in reverse reprojection caching.

Many other techniques take advantage of TC for stylized animations. For a detailed treatment of all these techniques, refer to the recent survey by Bérnard *et al.* [BBT11].

5.9. Level-of-detail

The idea behind discrete level-of-detail (LOD) techniques is to use a set of representations with differing complexities (levels of detail) for one model and select the most appropriate representation for rendering at runtime [LRC*02]. Complexity can, for instance, vary in the employed materials or shaders or in the amount of triangles used. Due to memory constraints and the effort involved in the creation process of LODs, usually, only a small number is employed, which can result in noticeable popping artefacts when switching from one representation to another. A theoretical solution would be to switch only when the respective pixel output of two representations is indistinguishable. This so-called late switching has practical problems. First, it is hard to guarantee equality in pixel output for a given view scenario and lighting without rendering both representations first, which, of course, defeats the purpose. Second, the idea of switching as late as possible counteracts the potential gain of employing LODs in the first place. In practice, switching is done as soon as 'acceptable'.



Figure 27: LOD interpolation combines two buffers containing the discrete LODs to create smooth LOD transitions. First and second column: buffers; last column: combination. The top row shows the two LODs in red and blue, respectively.

5.9.1. Discrete LOD blending

A more practical solution to this problem proposed by [GW06] is to include a transition phase during which both LODs are rendered and then blended into the final image [GW06]. Apart from other problems, this approach requires that the geometry (and the shaders) of both LODs have to be rendered in this transition phase, thereby generating a higher rendering cost than the higher quality level alone would incur. To circumvent this, Scherzer and Wimmer [SW08] introduced a solution that performs LOD interpolation (see Figure 27). The idea is that by using TC, the two LODs required during an LOD transition can be rendered in subsequent frames. Two separate render passes are used to achieve the transition phase between adjacent LOD representations: Pass 1 renders the scene into an off-screen buffer (called LOD buffer). For objects in transition, one of the two LOD representations is used and only a certain amount of its fragments are rendered (see Figure 28), depending on where in the transition (i.e. how visible) this object currently is. This is later repeated in the next frame using the other LOD representation and rendering into a second LOD buffer. The second pass combines these two LOD buffers (one from the current and one from the previous frame) to create the desired smooth transition effect.

5.9.2. LOD cuts

Another particular representation is the use of scene hierarchies for rendering purposes. The key idea is to represent a scene in form of a tree where each node stores an approximate scene representation for the given precision level corresponding to a level in the tree. While one could start the search for an appropriate cut (selection of nodes) for a given view from the top of the tree, this solution is often wasteful. A cut from one frame to the next rarely changes



Figure 28: Transition phase from LOD_k to LOD_{k+1} : left: LOD_k ; middle: midway in the transition all fragments of both LODs are drawn; right: LOD_{k+1} ; Below: First LOD_{k+1} is gradually introduced until all its fragments are drawn. Then, LOD_k is gradually removed by rendering fewer and fewer fragments. The top two rows show the result of our method and a false colour illustration.

significantly, as the view is very similar. Instead, a few local refinements are usually enough. Consequently, many LOD approaches rely on a cut from the previous frame to find the new representation [XV96, Hop97]. Due to the coherence from one frame to the next, it is sometimes even useful to enforce a limited number of local changes in order to bound the cost of each cut modification from one frame to the next. Therefore, such refinement strategies allow for an efficient GPU implementation on modern hardware [HREB11].

While we assumed here that the scene is entirely present in memory, for large scenes, this can actually become impossible. Nonetheless, as indicated above, only a small part of the tree is actually needed (a few nodes around the derived cut). Consequently, it is possible to restrict memory usage to a minimum by removing all unnecessary nodes. This principle leads to streaming solutions that we will investigate next.

5.10. Streaming

5.10.1. Large-data visualization

Streaming is a particularly challenging problem when dealing with large data sets. Efficiency is of paramount importance, especially due to the wealth of scanned data that are often tremendous in size. These difficult-to-render data sets exceed available memory capacities by far.

Usually, data structures are used to decompose the original data set in a hierarchical manner. The idea is to use structures that can be selectively refined. Once the right refinement scale is established for a view, only local modifications are applied to update the structure for the next frame, as seen previously for LODs. This lazy update scheme implicitly exploits TC because the modifications from one frame to the next can often be drastically limited. In some cases, even movement prediction can prove successful [LKR*96]. In any case, deriving an entirely new refinement would lead to a huge performance overhead.

These hierarchical data structures are further designed in a flexible way, in the sense that the actual geometric information is only added to the data structure when there it is requested during rendering. In fact, not all data are needed at each point in time, as for a given viewpoint, unnecessary details can be omitted using LOD schemes, as previously mentioned. In particular, the use of occlusion culling leads to a much smaller data subset that still produces a complete image.

We cannot completely explore in-depth all solutions that exist for the many different types of input data, varying from geometric models [WDS04], over point clouds [WBB*07], to recent volume-rendering approaches [GMAG08, CNLE09].

To illustrate the principle, we will base our discussion on ray-tracing queries. The main observation is that raytracing is a useful tool, not only to produce images, but also to determine data fetches [WDS04]. Typically, scenes are organized in form of a tree (Figure 29 illustrates several levels of detail corresponding to levels in this tree). Rays then traverse the tree and test geometry intersections in each traversed node. The idea is that initially each node of the tree can be empty and will only be filled progressively during rendering. Whenever a ray reaches such an empty node, a data request is triggered and the ray potentially stopped, or traced against a simplified representation that fits into memory. In this way, the rays themselves control the level of detail, as well as frustum culling, or occlusion tests. No special handling of acceleration techniques is needed and, in particular, as rays tend to vary little from one view to the next (e.g. for a small and purely rotational movement of the camera, many rays remain almost unchanged), the temporal redundancy is implicitly handled.

Such strategies have proven particularly efficient in the context of volume rendering [GMAG08, CNLE09]. Here, a multi-resolution data representation is arranged in the tree, and whenever data are missing, rays do not need to be cancelled, but can instead walk up the tree to access lower resolution versions of the data. To deal with the memory constraints, such algorithms typically employ an LRU cache mechanism (least-recently used), i.e. newly loaded elements will replace those that have not been accessed for a longer time. As elements tend to be active over coherent periods of time, such strategies prove particularly useful. They can be implemented



Figure 29: On the basis of volume-data streaming algorithms, it is a hierarchical scene representation. Here, several levels of detail are illustrated. The resolution is switched automatically during the ray-tracing step, depending on the distance. Not all data are in memory at once, only the parts that are actually currently under use reside in memory.

very efficiently on modern GPUs [CNSE10] and can even serve in the context of global illumination [CNS*11].

5.10.2. Remote rendering

Remote rendering is trend that is now receiving increased attention. Many companies such as OnLive, OTOY or Gaikai focus on the particular topic of game streaming. In such a scenario, it is vital to exploit TC in order to reduce bandwidth and computational effort on the server side.

In most cases, the underlying technology for game streaming is closely related to video compression, with a few exceptions, which transfer API calls directly to the client [NDS*08], but such an architecture assumes very advanced client hardware that can deal with all rendering commands.

Video-encoded rendering does not require a powerful client, but the bandwidth requirements can be high. Hence, temporal redundancy and perceptual limitations are a crucial component for such encoding algorithms. For example, it is possible to exploit the reduced accuracy of the human visual system to pre-filter in-between frames to reduce the required bandwidth [FB08].

Usually, video encoding makes use of so-called I-frames that are only internally encoded (i.e. do not rely on previous or future frames) and produce precise movie information. These I-frames are rare and completed by P-frames that rely on previous, and B-frames that make use of previous and following images. The latter type delivers quality-wise superior results, but is difficult to exploit for real-time applications. Because of the dependency on future frames, a delay is enforced, which can be particularly problematic for lower frame rates. Furthermore, in the extreme case, if a frame drop occurs, very noticeable artefacts can arise.

A complete survey of video encoding goes beyond the scope of this document. Here, we will describe some particular insights that relate to 3D rendering. Video compression for rendering should exploit the particularity of the content. One example is that many attributes can be extracted from the 3D scene itself, which can then be used to improve the compression algorithms. One can accelerate the encoding process through the use of object motion vectors [FE09] that are applied to predict pixel motion. The TC of the animation in the scene is directly exploited. This solution can be very successful and enable higher compression [WKC94] than standard matching techniques.

It is also possible to go further and rely on the scene attributes for reconstruction purposes. In fact, the previously discussed spatio-temporal upsampling strategies (Section 5.6) are very good candidates for application in a streaming context [PHE*11]. Such a combination has several advantages. Not only the bandwidth, but also the server workload is tackled (only small-resolution images are produced and transferred). Furthermore, as the previous frame is still present on the client when the new frame is supposed to be reconstructed, the algorithm can exploit this knowledge during compression and rely on these values as predictors for statistics-based encoding schemes [PHE*11].

This field of research is still relatively young and is likely to evolve significantly, but the mentioned recent advances illustrate the importance of exploiting TC in this context.

5.11. Online visibility culling

Culling techniques like view-frustum culling [AM00] and visibility culling are important acceleration techniques for rasterization-based real-time rendering. While visibility is often pre-processed in a lengthy offline step, online visibility culling algorithms compute visibility on the fly for the current viewpoint. Typically direct hardware queries are used, so-called *occlusion queries*. A common use of occlusion queries is to conservatively test the visibility of a simple *proxy geometry*, e.g. the bounding box of a more complex object.

5.11.1. Exploiting TC

The major challenge for any online culling algorithm is to reduce the overhead caused by the visibility calculations (the so-called occlusion queries), which can become unacceptable in situations when most objects in the scene are visible. Hence, it is vital to exploit TC, assuming that objects that are (in)visible in one frame are likely to remain (in)visible in future frames. Using TC, we can substantially reduce the number of issued occlusion queries, as well as hide their latency.

The following general strategy is implemented in different forms by all state-of-the-art occlusion culling algorithms: First, an algorithm establishes a visible front by rendering those objects that were visible in the previous frame. Then, it queries the visibility of the previously invisible objects against this visible front. Finally, to keep overdraw low, it updates the visibility classifications of the objects from the visible front. This can be done in a lazy manner, e.g. by querying each object every n frames (assuming coherence over several frames). The clever hierarchical z-buffer algorithm proposed by [GKM93] uses both spatial hierarchies and TC in the manner described above for maximal efficiency. To accelerate visibility queries, it maintains a twofold hierarchy—an image pyramid over the z-buffer and an octree hierarchy over the objects. The feasibility of this algorithm suffers from the drawback that only parts of it are supported by the hardware.

5.11.2. Coherent hierarchical culling (CHC)

Beginning with the NVIDIA GeForce 3 graphics card, hardware-accelerated occlusion queries can be issued for a batch of rendered geometry. While hardware occlusion queries are fast, the queries still come with a non-negligible cost, and they have a certain latency until the query result is available on the CPU. Algorithms like the CHC algorithm [BWPP04] utilize TC to avoid such CPU stalls and fill the latency in a meaningful way.

The algorithm exploits temporal and spatial coherence by identifying invisible subtrees. To avoid wasted interior node queries, it starts issuing queries at the previous cut in the hierarchy (i.e. it queries previously invisible subtrees and visible leaves). Furthermore, CHC assumes that previously visible leaves stay visible, and *never waits* for their query result. Instead, these nodes are *always* rendered in the current frame. Their visibility classifications are updated for the *next frame* once the result is available. For this purpose, the pending queries are managed in a dedicated *query queue*. Fortunately, hardware occlusion queries provide a cheap way to check if a query result is available. This way, it is possible to do some traversal and rendering on the CPU, while the GPU is busy computing the query results, avoiding CPU stalls and GPU starvation.

5.11.3. Making further use of TC

The original CHC algorithm works sufficiently well in many situations, but still suffers from considerable overhead because of the large overall number of queries and the relatively high cost of individual queries. The CHC++ algorithm [MBW08] addresses these drawbacks by making better use



Figure 30: Comparison of view frustum culling (VFC), view frustum culling and potentially visible sets (VFC+PVS), and online visibility culling using CHC++ [BMW*09].

of temporal and spatial coherence. It extends the CHC algorithm with a couple of simple but effective optimizations.

CHC++ issues *batches of queries* instead of individual queries. This is based on the observation that a huge portion of the individual query cost in CHC is caused by GPU state changes due to the constant interleaving of render and query mode (e.g. depth write on/off). The coherence among nodes in a batch is exploited by assuming that mutual occlusion of these nodes is not relevant.

CHC++ compiles *multi-queries*, which are able to cover more nodes by a single occlusion query. This method is able to reduce the number of queries for previously invisible nodes up to an order of magnitude by making better use of TC. The decision of including a node in a multi-query is based on its history. Nodes that were invisible for a long time are likely to stay invisible; hence, they can be handled by a single query. A failed multi-query means that the nodes must be tested individually, wasting one query while increasing the overall number of queries by one. Hence, the authors introduced a cost-benefit model (based on the likelihood of a node to stay invisible) which minimizes the number of queries. Note that the nodes can be spatially completely unrelated.

Lazily issuing queries for previously visible nodes every *n* frames (which was an option in CHC) has the danger of sudden frame rate drops. These happen because of many queries being issued in the same frame due to simultaneous visibility changes (e.g. all rooftops of a town become visible in the same frame). To avoid this negative effect of coherence, CHC++ applies a *temporally jittered* sampling pattern for scheduling those queries.

Figure 30 shows timings in the Powerplant scene with 12M triangles (using a NVIDIA GeForce 280 GTX). Interestingly, online visibility culling with CHC++ is typically faster than rendering based on *preprocessed* potentially visible sets (PVSs). This is because the computational

overhead of CHC++ is less than the rendering overhead due to the more conservative preprocessed visibility solution (i.e. it overestimates the objects visible from the current viewpoint as visibility is stored per region).

5.12. Temporal perception

This report presented several algorithms that exploit TC of data, leveraging the redundancy of information over time. But, in fact, TC can also be used in an inverse manner to produce richer content by exploiting elements of perception, which seems to be a very promising avenue for future endeavours. Even physically incoherent signals of high variance can be perceived as temporally coherent under certain circumstances. A simple example is a flash light strobing at very high frequency. At some point, we will no longer be able to see the flickering effect and perceive a coherent lighting. In fact, CRT screens made direct use of these observations. When working with such perceptual TC, many new possibilities become available. Here, we will focus on two examples (colour and resolution increase) that represent first steps in this direction of research.

One of the oldest examples to enrich graphics by exploiting temporal effects is to rely on flickering to increase the computer's colour palette. The most prominent representatives of such a technique are DLP projectors, which display, in a coherent way, the three colour channels of an image in rapid succession. These separate signals are then integrated by the eye so that an observer perceives a fully coloured image.

Similar to the DLP principle, one can increase the available colours of a screen or machine. Back when colour palettes were limited, having darkened tints of colours (e.g. for shadows) was not always possible. By flickering the corresponding elements on the screen, a simple solution to extend the palette was born. For an observer, these flickered colours mix because at higher frame rates, the eye no longer distinguishes each frame individually. The same procedure is often employed in LCD screens under the name of frame rate control. In practice, the material is often limited to 6 bits per colour channel, whereas the graphics card produces 8-bit colour channels. The solution is to represent fractional colours by displaying the immediate neighbours in quick succession over time [Art04]. Again, the eye integration delivers the illusion that what was observed on the retina is actually the fractional colour value.

Another way to influence colour perception involving the temporal domain is to make use of adaptation. When looking for a longer time at a bright source, the source imprints its image on our retina in form of an afterimage in opponent colours. This phenomenon relates to receptor bleaching. By making use of a computational model of this effect, the mechanism can be simulated and can lead to a perceived increase of brightness [RE12].

Besides more colours, resolution and details can also be addressed. It is known that object discrimination is more successful for sub-pixel camera panning than for corresponding static frames [KDT05, BSH06]. Didyk et al. [DER*10a] further explored this observation by taking into account the TC of eye movement for apparent resolution enhancement. In other words, they are able to produce the illusion of high resolution on a low-resolution screen, and thereby, even surpass the physical boundaries. More precisely, their setup is a low-resolution screen on which moving content is displayed at a high refresh rate. When the eye starts tracking the information on the screen, several frames will be successively integrated on the retina. By predicting the eye movement, it is possible to derive an image sequence such that the integrated response on the retina approaches a high-resolution image content. The accuracy of the tracking is assured by the human visual system's smooth-pursuit eye motion. This mechanism leads to an almost perfect stabilization for steady linear motion with velocities in the range of $0.625 - 2.5^{\circ}$ s^{-1} [LRP*06]. The low-resolution image sequence itself is derived using an optimization framework that takes eye integration and flicker perception into account to ensure that this sequence integrates properly on the retina. The solution has recently been extended to general animation sequences including arbitrary movements and general scenes by assuming the eye movement to be related to the underlying optical flow [TDR*11].

6. Summary

In this report, we have described real-time rendering techniques that take advantage of TC by reusing expensive calculations from previously rendered frames. As a result, both performance and quality of many common real-time rendering tasks can be improved.

We started by showing that real-time rendering applications exhibit a significant amount of spatio-TC, thus motivating data reuse in shading computations. We then briefly surveyed the historical approaches focused on offline methods before describing the real-time techniques which constitute the main focus of this report. We introduced the basic algorithm for performing real-time reprojection on the GPU. The approach allows the shader to efficiently query shading results from an earlier rendered frame (reverse reprojection), or similarly, map a shading result from the current frame to the next frame (forward reprojection). We then analyzed the quality versus speed trade-offs associated with data reuse.

We presented several applications that take advantage of data reuse. We started with the basic application of directly reusing results of an expensive shading computation, such as the previous results of a procedural noise shader. For applications that accumulate results from multiple renderings of the same scene, such as stereo, motion blur and depth-of-field rendering, we showed how to reuse shading results from a 'central frame' when rendering the remaining accumulated frames, thereby reducing rendering times considerably.

Some expensive per-pixel computations often require approximating an integral by combining multiple spatial samples, such as shadow computation. To address those scenarios, we described how to amortize computation by combining results from multiple frames in order to achieve better results for anti-aliasing, pixel-correct shadows and soft shadows, among other applications. Using reprojection for these techniques allows for a much larger number of samples for the same rendering time budget. The amortized approach also allows for a smoothly varying shading result instead of the 'all or nothing' reuse strategy of the earlier applications that either fully reuse the earlier results or compute it entirely anew. We showed significant improvement in quality and speed for these amortized approaches and analyzed the trade-off between lag and aliasing in the rendered result. We also showed how TC can be used to compute not only efficient shadows from a light source, but also efficient global illumination approximations through amortization. We then presented techniques to combine both spatial and temporal upsampling using a joint bilateral filter that considers samples from recently rendered frames, and how to increase frame rates by generating new intermediate frames by taking advantage of TC.

Finally, we showed how TC can be used to improve quality or accelerate a variety of tasks. Forward reprojection was applied to smoothly advect brush strokes for NPR of animated scenes. TC was used to render transition phases for discrete LOD blending, thereby avoiding popping artefacts and creating a smooth transition between levels of detail. We then showed how TC has also been explored for streaming content, such as improved compression for remote rendering of synthetic scenes (e.g. games), and large-data visualization. Another area that has been explored is how to use TC to accelerate occlusion culling. Finally, we showed techniques that consider elements of perception of the human visual system in order to increase the apparent number of colours and apparent resolution of the image.

To summarize, this report surveyed strategies for reusing shading computations during real-time rendering. These strategies are very generally applicable as demonstrated on a very large number of different application scenarios. While relatively recent, this research trend has already found uses in the gaming community. We hope that in this process, we have convinced the reader that taking advantage of TC can vastly reduce shading computation in a very large number of rendering scenarios. With the continued increase in complex shading effects, frame rates, screen resolution and rendering hardware features, we expect that techniques that take advantage of TC will become even more prevalent.

Acknowledgements

We would like to thank the Intel Visual Computing Institute (IVCI) at Saarland University, the French National Research Agency (iSpace&Time), the People Programme (Marie Curie Actions) of the FP7 (under REA Grant Agreement no. 290227) and the Austrian Science Fund (FWF) for partial funding of this work.

References

- [AH93] ADELSON S. J., HODGES L. F.: Stereoscopic raytracing. *The Visual Computer 10*, 3 (1993), 127–144.
- [AH95] ADELSON S. J., HODGES L. F.: Generating exact raytraced animation frames by reprojection. *IEEE Computer Graphics and Applications 15*, 3 (1995), 43–52.
- [AM00] ASSARSSON U., MÖLLER T.: Optimized view frustum culling algorithms for bounding boxes. *Journal of graphics, GPU, and game tools 5*, 1 (2000), 9–22.
- [And10] ANDREEV D.: Real-time frame rate up-conversion for video games. In *Proceedings of ACM SIGGRAPH 2010 Talks* (2010).
- [Art04] ARTAMONOV O.: X-bit's guide: Contemporary lcd monitor parameters and characteristics. http://www.xbitlabs.com/articles/monitors/display/lcdguide_11.html. Accessed October 2004.
- [ATS94] ARVO J., TORRANCE K., SMITS B.: A framework for the analysis of error in global illumination algorithms. In SIGGRAPH '94: Proceedings of the 21st Annual Conference on Computer Graphics and Interactive Techniques (New York, NY, USA, 1994), ACM, pp. 75–84.
- [BBT11] BÉNARD P., BOUSSEAU A., THOLLOT J.: State-ofthe-art report on temporal coherence for stylized animations. *Computer Graphics Forum 30*, 8 (December 2011), 2367–2386.
- [BCGF10] BÉNARD P., COLE F., GOLOVINSKIY A., FINKELSTEIN A.: Self-similar texture for coherent line stylization. In NPAR 2010: Proceedings of the 8th International Symposium on Non-photorealistic Animation and Rendering (New York, NY, USA, 2010), ACM Press, pp. 91–97.
- [BFMZ94] BISHOP G., FUCHS H., MCMILLAN L., ZAGIER E. J. S.: Frameless rendering: Double buffering considered harmful. In SIGGRAPH '94: Proceedings of the 21st Annual Conference on Computer Graphics and Interactive Techniques (New York, NY, USA, 1994), ACM, pp. 175–176.
- [BFP*11] BUCHHOLZ B., FARAJ N., PARIS S., EISEMANN E., BOUBEKEUR T.: Spatio-temporal analysis for

parameterizing animated lines. In *Proceedings of the International Symposium on Non-Photorealistic Animation and Rendering (NPAR)* (2011).

- [BJ88] BADT Jr. S.: Two algorithms for taking advantage of temporal coherence in ray tracing. *The Visual Computer* 4 (1988), 123–132.
- [BM05] BENNETT E. P., MCMILLAN L.: Video enhancement using per-pixel virtual exposures. *ACM Transactions on Graphics 24*, 3 (2005), 845–852.
- [BMW*09] BITTNER J., MATTAUSCH O., WONKA P., HAVRAN V., WIMMER M.: Adaptive global visibility sampling. In *SIGGRAPH '09: Proceedings of the ACM SIGGRAPH 2009 Papers* (New York, NY, USA, 2009), ACM.
- [BSD08] BAVOIL L., SAINZ M., DIMITROV R.: Image-space horizon-based ambient occlusion. In *SIGGRAPH '08: Proceedings of the ACM SIGGRAPH 2008 talks* (2008).
- [BSH06] BIJL P., SCHUTTE K., HOGERVORST M. A.: Applicability of TOD, MTDP, MRT and DMRT for dynamic image enhancement techniques. In *Proceedings of the Society of Photo-Optical Instrumentation Engineers (SPIE) Conference Series* (2006), vol. 6207.
- [BWPP04] BITTNER J., WIMMER M., PIRINGER H., PURGATHOFER W.: Coherent hierarchical culling: Hardware occlusion queries made useful. *Computer Graphics Forum 23*, 3 (September 2004), 615–624. [Proceedings EUROGRAPHICS 2004.]
- [CNLE09] CRASSIN C., NEYRET F., LEFEBVRE S., EISEMANN E.: Gigavoxels : Ray-guided streaming for efficient and detailed voxel rendering. In *Proceedings of the ACM SIGGRAPH Symposium on Interactive 3D Graphics and Games (I3D)* (Boston, MA, USA, February 2009), ACM Press.
- [CNS*11] CRASSIN C., NEYRET F., SAINZ M., GREEN S., EISEMANN E.: Interactive indirect illumination using voxel cone tracing. *Computer Graphics Forum 30*, 7 (2011), pp. 1921–1930. doi: 10.1111/j.1467-8659.2011.02063.x.
- [CNSE10] CRASSIN C., NEYRET F., SAINZ M., EISEMANN E.: Efficient Rendering of Highly Detailed Volumetric Scenes with GigaVoxels. In *GPU Pro.* A. K. Peters (Ed.), Natick, MA, USA, (2010), ch. X.3, pp. 643–676.
- [CT81] COOK R. L., TORRANCE K. E.: A reflectance model for computer graphics. In SIGGRAPH'81: Proceedings of the 8th Annual Conference on Computer Graphics and Interactive Techniques (New York, NY, USA, 1981), ACM, pp. 307–316.
- [CW93] CHEN S. E., WILLIAMS L.: View interpolation for image synthesis. In SIGGRAPH '93: Proceedings of the 20th

Annual Conference on Computer Graphics and Interactive Techniques (New York, NY, USA, 1993), ACM, pp. 279–288.

- [DDM03] DAMEZ C., DMITRIEV K., MYSZKOWSKI K.: State of the art in global illumination for interactive applications and high-quality animations. *Computer Graphics Forum* 22, 1 (March 2003), 55–77.
- [DER*10a] DIDYK P., EISEMANN E., RITSCHEL T., MYSZKOWSKI K., SEIDEL H.-P.: Apparent display resolution enhancement for moving images. ACM Transactions on Graphics (Proceedings of SIGGRAPH 2010, Los Angeles) 29, 3 (2010).
- [DER*10b] DIDYK P., EISEMANN E., RITSCHEL T., MYSZKOWSKI K., SEIDEL H.-P.: Perceptually-motivated real-time temporal upsampling of 3D content for high-refresh-rate displays. *Computer Graphics Forum* 29, 2 (2010), 713–722.
- [DRE*10] DIDYK P., RITSCHEL T., EISEMANN E., MYSZKOWSKI K., SEIDEL H.-P.: Adaptive image-space stereo view synthesis. In *Proceedings of the Vision, Modeling and Visualization Workshop* (11 2010).
- [DWWL05] DAYAL A., WOOLLEY C., WATSON B., LUEBKE D. P.: Adaptive frameless rendering. In Proceedings of the Eurographics Symposium on Rendering Techniques, Konstanz, Germany, June 29–July 1, 2005 (2005), O. Deussen, A. Keller, K. Bala, P. D. D. W. Fellner, S. N. Spencer (Eds.). Eurographics Association, Konstanz, Germany, pp. 265–275.
- [EASW09] EISEMANN E., ASSARSSON U., SCHWARZ M., WIMMER M.: Casting shadows in real time. In *Proceedings of the ACM SIGGRAPH Asia 2009 Courses* (Dec. 2009).
- [EASW10] EISEMANN E., ASSARSSON U., SCHWARZ M., WIMMER M.: Shadow algorithms for real-time rendering. In *Proceedings of the Eurographics Tutorial* (Dec. 2010).
- [ED04] EISEMANN E., DURAND F.: Flash photography enhancement via intrinsic relighting. ACM Transactions on Graphics (Proceedings of Siggraph Conference) 23 (2004), 673–678.
- [ED07a] EISEMANN E., DÉCORET X.: On exact error bounds for view-dependent simplification. *Computer Graphics Forum* 26, 2 (2007), 202–213.
- [ED07b] EISEMANN E., DÉCORET X.: Visibility sampling on gpu and applications. *Computer Graphics Forum (Proceedings of Eurographics 2007)* 26, 3 (2007), 535–544.
- [ESAW11] EISEMANN E., SCHWARZ M., ASSARSSON U., WIMMER M.: *Real-Time Shadows*. A. K. Peters (Ed.). CRC Press, Natick, MA, USA, (2011).

- [FB08] FUJIBAYASHI A., BOON C. S.: A masking model for motion sharpening phenomenon in video sequences. *IE-ICE Transactions on Fundamentals of Electronics, Communications and Computer Sciences E91-A*, 6 (2008), 1408–1415.
- [FC08] Fox M., COMPTON S.: Ambient occlusive crease shading. *Game Developer Magazine* (March 2008).
- [FE09] FECHTELER P., EISERT P.: Depth map enhanced macroblock partitioning for H.264 video coding of computer graphics content. In *Proceedings of the International Conference on Image Processing* (2009), pp. 3441–3444.
- [FPD08] FENG X.-F., PAN H., DALY S.: Comparisons of motion-blur assessment strategies for newly emergent LCD and backlight driving technologies. *Journal of the Society for Information Display 16* (2008), 981–988.
- [GKM93] GREENE N., KASS M., MILLER G.: Hierarchical Zbuffer visibility. *Computer Graphics (Proceedings of SIG-GRAPH '93)* (1993), 231–238.
- [GMAG08] GOBBETTI E., MARTON F., ANTONIO J., GUITIAN I.: A single-pass GPU ray casting framework for interactive out-of-core rendering of massive volumetric datasets. *The Visual Computer 24*, 7 (2008), 797–806.
- [GW06] GIEGL M., WIMMER M.: Unpopping: Solving the image-space blend problem for smooth discrete lod transitions. *Computer Graphics Forum* 26, 1 (Mar. 2006), 46–49.
- [HA90] HAEBERLI P., AKELEY K.: The accumulation buffer: Hardware support for high-quality rendering. In *Proceed*ings of SIGGRAPH '90 (New York, NY, USA, 1990), ACM, pp. 309–318.
- [HBS03] HAVRAN V., BITTNER J., SEIDEL H.-P.: Exploiting temporal coherence in ray casted walkthroughs. In SCCG '03: Proceedings of the 19th Spring Conference on Computer Graphics (New York, NY, USA, 2003), ACM Press, pp. 149–155.
- [HDMS03] HAVRAN V., DAMEZ C., MYSZKOWSKI K., SEIDEL H.-P.: An efficient spatio-temporal architecture for animation rendering. In *EGRW '03: Proceedings of the 14th Eurographics Workshop on Rendering* (Aire-la-Ville, Switzerland, 2003), Springer, pp. 106–117.
- [HEMS10] HERZOG R., EISEMANN E., MYSZKOWSKI K., SEIDEL H.-P.: Spatio-temporal upsampling on the GPU. In *Proceedings of the Symposium on Interactive 3D Graphics and Games* (New York, NY, USA, 2010), ACM.
- [HH97] HECKBERT P. S., HERF M.: Simulating Soft Shadows with Graphics Hardware. Tech. Rep. CMU-CS-97-104,

CS Department, Carnegie Mellon University, Jan. 1997. http://www.cs.cmu.edu/ ph.

- [HLHS03] HASENFRATZ J.-M., LAPIERRE M., HOLZSCHUCH N., SILLION F.: A survey of real-time soft shadows algorithms. *Computer Graphics Forum 22*, 4 (Dec. 2003), 753–774. [State-of-the-Art Reviews.]
- [Hop97] HOPPE H.: View-dependent refinement of progressive meshes. In *Proceedings of SIGGRAPH* (1997).
- [HREB11] HOLLÄNDER M., RITSCHEL T., EISEMANN E., BOUBEKEUR T.: Manylods: Parallel many-view level-ofdetail selection for real-time global illumination. *Computer Graphics Forum (Proc. of EGSR)* (2011).
- [Jan01] JANSSEN R.: *Computational Image Quality*. Spie Press, Bellingham, Washington, DC, 2001.
- [Kaj86] KAJIYA J. T.: The rendering equation. *SIGGRAPH Computer Graphics 20*, 4 (1986), 143–150.
- [KCLU07] KOPF J., COHEN M. F., LISCHINSKI D., UYTTENDAELE M.: Joint bilateral upsampling. ACM Transactions on Graphics (Proceedings of SIGGRAPH 2007) 26, 3 (2007).
- [KDMF03] KALNINS R. D., DAVIDSON P. L., MARKOSIAN L., FINKELSTEIN A.: Coherent stylized silhouettes. *ACM Transactions on Graphics* 22, 3 (July 2003), 856–861.
- [KDT05] KRAPELS K., DRIGGERS R. G., TEANEY B.: Targetacquisition performance in undersampled infrared imagers: Static imagery to motion video. *Applied Optics* 44, 33 (2005), 7055–7061.
- [Kel97] KELLER A.: Instant radiosity. In Proceedings of SIG-GRAPH ' 97 (Aug. 1997), Computer Graphics Proceedings, Annual Conference Series, pp. 49–56.
- [KMM*02] KALNINS R. D., MARKOSIAN L., MEIER B. J., KOWALSKI M. A., LEE J. C., DAVIDSON P. L., WEBB M., HUGHES J. F., FINKELSTEIN A.: WYSIWYG NPR: Drawing strokes directly on 3D models. ACM Transactions on Graphics 21, 3 (July 2002), 755–762.
- [KP11] KASS M., PESARE D.: Coherent noise for nonphotorealistic rendering. ACM Transactions on Graphics 30, 4 (Aug. 2011), 30:1–30:6.
- [KTM*10] KNECHT M., TRAXLER C., MATTAUSCH O., PURGATHOFER W., WIMMER M.: Differential instant radiosity for mixed reality. In Proceedings of the Ninth IEEE and ACM International Symposium on Mixed and Augmented Reality (ISMAR'10) (Seoul, Korea, October 2010).

- [KV04] KLOMPENHOUWER M. A., VELTHOVEN L. J.: Motion blur reduction for liquid crystal displays: Motioncompensated inverse filtering. In *Proc. SPIE*, 5308, (2004), pp. 690–699.
- [Lan02] LANDIS H.: Production-ready global illumination. In Proceedings of the Conference on SIGGRAPH 2002 Course Notes 16 (2002), 2002.
- [LKR*96] LINDSTROM P., KOLLER D., RIBARSKY W., HODGES L. F., FAUST N., TURNER G. A.: Real-time, continuous level of detail rendering of height fields. In *Proceedings of SIG-GRAPH* (1996), pp. 109–118.
- [LRC*02] LUEBKE D., REDDY, M., COHEN J., VARSHNEY A., WATSON B., HUEBNER R.: Level of Detail for 3D Graphics. Morgan Kaufmann, New York, NY, USA, 2002.
- [LRP*06] LAIRD J., ROSEN M., PELZ J., MONTAG E., DALY S.: Spatio-velocity CSF as a function of retinal velocity using unstabilized stimuli. In *Proceedings of the Human Vision and Electronic Imaging XI* (2006), vol. 6057 of *SPIE Proceedings Series*, pp. 32–43.
- [LS97] LENGYEL J., SNYDER J.: Rendering with coherent layers. In SIGGRAPH '97: Proceedings of the 24th Annual Conference on Computer Graphics and Interactive Techniques (New York, NY, USA, 1997), ACM Press/Addison-Wesley Publishing Co., pp. 233–242.
- [LSF10] LU J., SANDER P. V., FINKELSTEIN A.: Interactive painterly stylization of images, videos and 3d animations. In *Proceedings of the Symposium on Interactive 3D Graphics and Games* (2010), pp. 127–134.
- [LSK*07] LAINE S., SARANSAARI H., KONTKANEN J., LEHTINEN J., AILA T.: Incremental instant radiosity for real-time indirect illumination. In *Proceedings of Eurographics Symposium on Rendering 2007* (2007), Eurographics Association, pp. 277–286.
- [MB95] MCMILLAN L., BISHOP G.: Head-tracked stereoscopic display using image warping. In *Proceedings of SPIE* (1995), Vol. 2409, pp. 21–30.
- [MBW08] MATTAUSCH O., BITTNER J., WIMMER M.: Chc++: Coherent hierarchical culling revisited. *Computer Graphics Forum (Proceedings of Eurographics 2008) 27*, 3 (Apr. 2008), 221–230.
- [Mit07] MITTRING M.: Finding next gen cryengine 2. In Proceedings of the Conference on SIGGRAPH 2007 Course Notes, Course 28, Advanced Real-Time Rendering in 3D Graphics and Games, (New York, NY, USA, 2007), ACM Press, pp. 97–121.
- [MKC07] MARROQUIM R., KRAUS M., CAVALCANTI P. R.: Efficient point-based rendering using image reconstruction.

In Proceedings of the Eurographics Symposium on Point-Based Graphics (2007), pp. 101–108.

- [MSW10] MATTAUSCH O., SCHERZER D., WIMMER M.: Highquality screen-space ambient occlusion using temporal coherence. *Computer Graphics Forum 29*(8) (2010), 2492–2503.
- [NDS*08] NAVE I., DAVID H., SHANI A., LAIKARI A., EISERT P., FECHTELER P.: Games@Large graphics streaming architecture. In *Proceedings of the Symposium on Consumer Electronics (ISCE)* (2008).
- [NSL*07] NEHAB D., SANDER P. V., LAWRENCE J., TATARCHUK N., ISIDORO J. R.: Accelerating real-time shading with reverse reprojection caching. In *Proceedings of the* 22nd ACM SIGGRAPH/EUROGRAPHICS Symposium on Graphics Hardware (2007), pp. 25–35.
- [PFD05] PAN H., FENG X.-F., DALY S.: LCD motion blur modeling and analysis. In *Proceedings of ICIP* (2005), pp. 21–24.
- [PHE*11] PAJAK D., HERZOG R., EISEMANN E., MYSZKOWSKI K., SEIDEL H.-P.: Scalable remote rendering with depth and motion-flow augmented streaming. *Computer Graphics Forum 30*, 2 (2011). (Proc. of Eurographics.)
- [PSA*04] PETSCHNIGG G., SZELISKI R., AGRAWALA M., COHEN M., HOPPE H., TOYAMA K.: Digital photography with flash and no-flash image pairs. ACM Transactions on Graphics (Proceedings of Siggraph Conference) 23, 3 (2004), 664–672.
- [QWQK00] Qu H., WAN M., QIN J., KAUFMAN A.: Image based rendering with stable frame rates. In VISUALIZA-TION '00: Proceedings of the 11th IEEE Visualization 2000 Conference (VIS 2000) (Washington, DC, USA, 2000), IEEE Computer Society.
- [RE12] RITSCHEL T., EISEMANN E.: A computational model of afterimages. *Computer Graphics Forum (Proc. EURO-GRAPHICS)* 31, 2 (May 2012).
- [REH*11] RITSCHEL T., EISEMANN E., HA I., SEIDEL H.-P.: Making imperfect shadow maps view-adaptive: Highquality global illumination in large dynamic scenes. *Computer Graphics Forum (presented at EGSR 2011)* (2011).
- [RGK*08] RITSCHEL T., GROSCH T., KIM M. H., SEIDEL H.-P., DACHSBACHER C., KAUTZ J.: Imperfect shadow maps for efficient computation of indirect illumination. ACM Transactions on Graphics (Proc. SIGGRAPH ASIA 2008) 27, 5 (2008), 129.
- [RP94] REGAN M., POSE R.: Priority rendering with a virtual reality address recalculation pipeline. In SIGGRAPH '94: Proceedings of the 21st Annual Conference on

Computer Graphics and Interactive Techniques (New York, NY, USA, 1994), ACM, pp. 155–162.

- [SaLY*08a] SITTHI-AMORN P., LAWRENCE J., YANG L., SANDER P. V., NEHAB D.: An improved shading cache for modern GPUs. In *Proceedings of Graphics Hardware* (2008), pp. 95–101.
- [SaLY*08b] SITTHI-AMORN P., LAWRENCE J., YANG L., SANDER P. V., NEHAB D., XI J.: Automated reprojection-based pixel shader optimization. ACM Transactions on Graphics 27, 5 (12 2008), 127.
- [SB95] SMITH S. M., BRADY J. M.: SUSAN—A new approach to low level image processing. Tech. Rep. TR95SMS1c, Chertsey, Surrey, UK, 1995.
- [Sch96] SCHAUFLER G.: Exploiting frame to frame coherence in a virtual reality system. In VRAIS '96: Proceedings of the 1996 Virtual Reality Annual International Symposium (VRAIS 96) (Washington, DC, USA, 1996), IEEE Computer Society, p. 95.
- [SEA08] SINTORN E., EISEMANN E., ASSARSSON U.: Samplebased visibility for soft shadows using alias-free shadow maps. Computer Graphics Forum (Proceedings of the Eurographics Symposium on Rendering 2008) 27, 4 (June 2008), 1285–1292.
- [SGHS98] SHADE J., GORTLER S., HE L.-W., SZELISKI R.: Layered depth images. In SIGGRAPH '98: Proceedings of the 25th Annual Conference on Computer Graphics and Interactive Techniques (New York, NY, USA, 1998), ACM, pp. 231–242.
- [Shi95] SHINYA M.: Improvements on the Pixel-tracing Filter: Reflection/Refraction, Shadows, and Jittering. In *Proceedings of the Graphics Interface '95* (1995), pp. 92– 102.
- [SJW07] SCHERZER D., JESCHKE S., WIMMER M.: Pixel-correct shadow maps with temporal reprojection and shadow test confidence. In *Proceedings of the Eurographics Sympo*sium on Rendering (2007), pp. 45–50.
- [SKUT*10] SZIRMAY-KALOS L., UMENHOFFER T., TOTH B., SZECSI L., SBERT M.: Volumetric ambient occlusion for real-time rendering and games. *IEEE Computer Graphics* and Applications 30 (2010), 70–79.
- [SLS*96] SHADE J., LISCHINSKI D., SALESIN D. H., DEROSE T., SNYDER J.: Hierarchical image caching for accelerated walkthroughs of complex environments. In SIGGRAPH '96: Proceedings of the 23rd Annual Conference on Computer Graphics and Interactive Techniques (New York, NY, USA, 1996), ACM, pp. 75–82.

- [SS00] SIMMONS M., SÉQUIN C. H.: Tapestry: A dynamic mesh-based display representation for interactive rendering. In *Proceedings of the 11th Eurographics Workshop* on Rendering (2000), pp. 329–340.
- [SSMW09] SCHERZER D., SCHWÄRZLER M., MATTAUSCH O., WIMMER M.: Real-time soft shadows using temporal coherence. *Lecture Notes in Computer Science (LNCS)* (Nov. 2009).
- [SSS74] SUTHERLAND I. E., SPROULL R. F., SCHUMACKER R. A.: A characterization of ten hidden surface algorithms. ACM Computing Surveys 6, 1 (1974), 1–55.
- [SW08] SCHERZER D., WIMMER M.: Frame sequential interpolation for discrete level-of-detail rendering. *Computer Graphics Forum (Proceedings EGSR 2008) 27*, 4 (June 2008), 1175–1181.
- [SW09] SMEDBERG N., WRIGHT D.: Rendering techniques in gears of war 2. *Lecture Notes in Computer Science* (2009).
- [SWP11] SCHERZER D., WIMMER M., PURGATHOFER W.: A survey of real-time hard shadow mapping methods. *Computer Graphics Forum 30*, 1 (Feb. 2011), 169–186.
- [TDR*11] TEMPLIN K., DIDYK P., RITSCHEL T., EISEMANN E., MYSZKOWSKI K., SEIDEL H.-P.: Apparent resolution enhancement for animations. In *Proceedings of the 27th Spring Conference on Computer Graphics* (Vinicne, Slovak Republic, 2011), pp. 85–92.
- [Tek95] TEKALP A. M.: Digital Video Processing. Prentice Hall, New York, NY, USA, 1995.
- [TM98] TOMASI C., MANDUCHI R.: Bilateral filtering for gray and color images. In *Proceedings of the ICCV* (1998), pp. 839–846.
- [TV05] TAKEUCHI T., VALOIS K. D.: Sharpening image motion based on the spatio-temporal characteristics of human vision. In *Proc. SPIE*, *Vol. 5666*, 690 (2005), pp. 83–94.
- [VALBW06] VELÁZQUEZ-ARMENDÁRIZ E., LEE E., BALA K., WALTER B.: Implementing the render cache and the edge-and-point image on graphics hardware. In *GI '06: Proceedings of Graphics Interface 2006* (Toronto, ON, Canada, 2006), Canadian Information Processing Society, pp. 211–217.
- [WBB*07] WAND M., BERNER A., BOKELOH M., FLECK A., HOFFMANN M., JENKE P., MAIER B., STANEKER D., SCHILLING A.: Interactive editing of large point clouds. In Proceedings of the Symposium on Point-Based Graphics 2007 : Eurographics/IEEE VGTC Symposium Proceedings (Prague, Czech Republik, 2007), B. Chen,

M. Zwicker, M. Botsch and R. Pajarola R. (Eds.), Eurographics Association, pp. 37–46.

- [WDG02] WALTER B., DRETTAKIS G., GREENBERG D. P.: Enhancing and optimizing the render cache. In EGRW '02: Proceedings of the 13th Eurographics Workshop on Rendering (Aire-la Ville, Switzerland, 2002), Eurographics Association, pp. 37–42.
- [WDP99] WALTER B., DRETTAKIS G., PARKER S.: Interactive rendering using the render cache. In *Rendering techniques* '99 (Proceedings of the 10th Eurographics Workshop on Rendering) (New York, NY, USA, Jun 1999), D. Lischinski and G. Larson (Eds.), vol. 10, Springer-Verlag/Wien, pp. 235–246.
- [WDS04] WALD I., DIETRICH A., SLUSALLEK P.: An interactive out-of-core rendering framework for visualizing massively complex models. In *Proceedings of the Eurographics Symposium on Rendering* (2004).
- [WGS99] WIMMER M., GIEGL M., SCHMALSTIEG D.: Fast walkthroughs with image caches and ray casting. In Virtual Environments '99: Proceedings of the 5th Eurographics Workshop on Virtual Environments (June 1999), M. Gervautz, D. Schmalstieg., and A. Hildebrand (Eds.), Eurographics, Springer-Verlag Wien, pp. 73–84. (ISBN 3-211-83347-1)
- [WKC94] WALLACH D. S., KUNAPALLI S., COHEN M. F.: Accelerated MPEG compression of dynamic polygonal scenes. In *Proceedings of SIGGRAPH* (1994), pp. 193–197.
- [WS99] WARD G., SIMMONS M.: The holodeck ray cache: An interactive rendering system for global illumination in nondiffuse environments. ACM Transactions on Graphics 18, 4 (1999), 361–368.

- [WSP04] WIMMER M., SCHERZER D., PURGATHOFER W.: Light space perspective shadow maps. In *Rendering Techniques 2004 (Proceedings of the Eurographics Symposium on Rendering)* (June 2004), A. Keller and H. W. Jensen (Eds.), Eurographics, Eurographics Association, pp. 143–151.
- [XV96] XIA J. C., VARSHNEY A.: Dynamic viewdependent simplification for polygonal models. In *IEEE Visualization '96* (1996), R. Yagel and G. M. Nielson (Eds.), pp. 335–344.
- [YNS*09] YANG L., NEHAB D., SANDER P. V., SITTHI-AMORN P., LAWRENCE J., HOPPE H.: Amortized supersampling. ACM Transactions on Graphics 28, 5 (2009), 135.
- [YSL08] YANG L., SANDER P. V., LAWRENCE J.: Geometryaware framebuffer level of detail. *Computer Graphics Forum* 27, 4 (2008), 1183–1188.
- [YTS*11] YANG L., TSE Y.-C., SANDER P. V., LAWRENCE J., NEHAB D., HOPPE H., WILKINS C. L.: Image-based bidirectional scene reprojection. ACM Transactions on Graphics 30, 6 (2011), 150.
- [YWY10] YU X., WANG R., YU J.: Real-time depth of field rendering via dynamic light field generation and filtering. *Computer Graphics Forum (Proc. of Pacific Graphics) 29*, 7 (2010).
- [ZMHI97] ZHANG H., MANOCHA D., HUDSON T., HOFF III K. E.: Visibility culling using hierarchical occlusion maps. In *Proceedings of SIGGRAPH* (1997), pp. 77–88.
- [ZWL05] ZHU T., WANG R., LUEBKE D.: A gpu-accelerated render cache. *Pacific Graphics (Short Paper Session)* (October 2005).